PHILIPPINE BIDDING DOCUMENTS

(As Harmonized with Development Partners)

Procurement of Waterworks Equipment

ITB-18STF-23 Sixth Edition July 2020

Preface

These Philippine Bidding Documents (PBDs) for the procurement of Goods through Competitive Bidding have been prepared by the Government of the Philippines for use by any branch, constitutional commission or office, agency, department, bureau, office, or instrumentality of the Government of the Philippines, National Government Agencies, including Government-Owned and/or Controlled Corporations, Government Financing Institutions, State Universities and Colleges, and Local Government Unit. The procedures and practices presented in this document have been developed through broad experience, and are for mandatory use in projects that are financed in whole or in part by the Government of the Philippines or any foreign government/foreign or international financing institution in accordance with the provisions of the 2016 revised Implementing Rules and Regulations of Republic Act No. 9184.

The Bidding Documents shall clearly and adequately define, among others: (i) the objectives, scope, and expected outputs and/or results of the proposed contract or Framework Agreement, as the case may be; (ii) the eligibility requirements of Bidders; (iii) the expected contract or Framework Agreement duration, the estimated quantity in the case of procurement of goods, delivery schedule and/or time frame; and (iv) the obligations, duties, and/or functions of the winning bidder.

Care should be taken to check the relevance of the provisions of the PBDs against the requirements of the specific Goods to be procured. If duplication of a subject is inevitable in other sections of the document prepared by the Procuring Entity, care must be exercised to avoid contradictions between clauses dealing with the same matter.

Moreover, each section is prepared with notes intended only as information for the Procuring Entity or the person drafting the Bidding Documents. They shall not be included in the final documents. The following general directions should be observed when using the documents:

a. All the documents listed in the Table of Contents are normally required for the procurement of Goods. However, they should be adapted as necessary to the circumstances of the particular Procurement Project.

- b. Specific details, such as the "*name of the Procuring Entity*" and "*address for bid submission*," should be furnished in the Instructions to Bidders, Bid Data Sheet, and Special Conditions of Contract. The final documents should contain neither blank spaces nor options.
- c. This Preface and the footnotes or notes in italics included in the Invitation to Bid, Bid Data Sheet, General Conditions of Contract, Special Conditions of Contract, Schedule of Requirements, and Specifications are not part of the text of the final document, although they contain instructions that the Procuring Entity should strictly follow.
- d. The cover should be modified as required to identify the Bidding Documents as to the Procurement Project, Project Identification Number, and Procuring Entity, in addition to the date of issue.
- e. Modifications for specific Procurement Project details should be provided in the Special Conditions of Contract as amendments to the Conditions of Contract. For easy completion, whenever reference has to be made to specific clauses in the Bid Data Sheet or Special Conditions of Contract, these terms shall be printed in bold typeface on Sections I (Instructions to Bidders) and III (General Conditions of Contract), respectively.
- f. For guidelines on the use of Bidding Forms and the procurement of Foreign-Assisted Projects, these will be covered by a separate issuance of the Government Procurement Policy Board.

Table of Contents

Gloss	ary of Acronyms, Terms, and Abbreviations	4
Sectio	n I. Invitation to Bid	8
Sectio	n II. Instructions to Bidders	13
1.	Scope of Bid	14
2.	Funding Information	14
3.	Bidding Requirements	14
4.	Corrupt, Fraudulent, Collusive, and Coercive Practices	15
5.	Eligible Bidders	
6.	Origin of Goods	16
7.	Subcontracts	16
8.	Pre-Bid Conference	
9.	Clarification and Amendment of Bidding Documents	
10.	Documents comprising the Bid: Eligibility and Technical Components	17
11.	Documents comprising the Bid: Financial Component	17
12.	Bid Prices	18
13.	Bid and Payment Currencies	19
14.	Bid Security	
15.	Sealing and Marking of Bids	
16.	Deadline for Submission of Bids	20
17.	Opening and Preliminary Examination of Bids	
18.	Domestic Preference	
19.	Detailed Evaluation and Comparison of Bids	
20.	Post-Qualification	
21.	Signing of the Contract	
Sectio	n III. Bid Data Sheet	23
Sectio	n IV. General Conditions of Contract	
1.	Scope of Contract	29
2.	Advance Payment and Terms of Payment	29
3.	Performance Security	30
4.	Inspection and Tests	30
5.	Warranty	30
6.	Liability of the Supplier	31
Sectio	n V. Special Conditions of Contract	32
Sectio	n VI. Schedule of Requirements	37
	n VII. Technical Specifications	
	n VIII. Checklist of Technical and Financial Documents	

Glossary of Acronyms, Terms, and Abbreviations

ABC – Approved Budget for the Contract.

BAC – Bids and Awards Committee.

Bid – A signed offer or proposal to undertake a contract submitted by a bidder in response to and in consonance with the requirements of the bidding documents. Also referred to as *Proposal* and *Tender*. (2016 revised IRR, Section 5[c])

Bidder – Refers to a contractor, manufacturer, supplier, distributor and/or consultant who submits a bid in response to the requirements of the Bidding Documents. (2016 revised IRR, Section 5[d])

Bidding Documents – The documents issued by the Procuring Entity as the bases for bids, furnishing all information necessary for a prospective bidder to prepare a bid for the Goods, Infrastructure Projects, and/or Consulting Services required by the Procuring Entity. (2016 revised IRR, Section 5[e])

BIR – Bureau of Internal Revenue.

BSP – Bangko Sentral ng Pilipinas.

Consulting Services – Refer to services for Infrastructure Projects and other types of projects or activities of the GOP requiring adequate external technical and professional expertise that are beyond the capability and/or capacity of the GOP to undertake such as, but not limited to: (i) advisory and review services; (ii) pre-investment or feasibility studies; (iii) design; (iv) construction supervision; (v) management and related services; and (vi) other technical services or special studies. (2016 revised IRR, Section 5[i])

CDA - Cooperative Development Authority.

Contract – Refers to the agreement entered into between the Procuring Entity and the Supplier or Manufacturer or Distributor or Service Provider for procurement of Goods and Services; Contractor for Procurement of Infrastructure Projects; or Consultant or Consulting Firm for Procurement of Consulting Services; as the case may be, as recorded in the Contract Form signed by the parties, including all attachments and appendices thereto and all documents incorporated by reference therein.

CIF – Cost Insurance and Freight.

CIP – Carriage and Insurance Paid.

CPI – Consumer Price Index.

DDP – Refers to the quoted price of the Goods, which means "delivered duty paid."

DTI – Department of Trade and Industry.

EXW – Ex works.

FCA – "Free Carrier" shipping point.

FOB – "Free on Board" shipping point.

Foreign-funded Procurement or Foreign-Assisted Project– Refers to procurement whose funding source is from a foreign government, foreign or international financing institution as specified in the Treaty or International or Executive Agreement. (2016 revised IRR, Section 5[b]).

Framework Agreement – Refers to a written agreement between a procuring entity and a supplier or service provider that identifies the terms and conditions, under which specific purchases, otherwise known as "Call-Offs," are made for the duration of the agreement. It is in the nature of an option contract between the procuring entity and the bidder(s) granting the procuring entity the option to either place an order for any of the goods or services identified in the Framework Agreement List or not buy at all, within a minimum period of one (1) year to a maximum period of three (3) years. (GPPB Resolution No. 27-2019)

GFI – Government Financial Institution.

GOCC – Government-owned and/or –controlled corporation.

Goods – Refer to all items, supplies, materials and general support services, except Consulting Services and Infrastructure Projects, which may be needed in the transaction of public businesses or in the pursuit of any government undertaking, project or activity, whether in the nature of equipment, furniture, stationery, materials for construction, or personal property of any kind, including non-personal or contractual services such as the repair and maintenance of equipment and furniture, as well as trucking, hauling, janitorial, security, and related or analogous services, as well as procurement of materials and supplies provided by the Procuring Entity for such services. The term "related" or "analogous services" shall include, but is not limited to, lease or purchase of office space, media advertisements, health maintenance services, and other services essential to the operation of the Procuring Entity. (2016 revised IRR, Section 5[r])

GOP – Government of the Philippines.

GPPB – Government Procurement Policy Board.

INCOTERMS – International Commercial Terms.

Infrastructure Projects – Include the construction, improvement, rehabilitation, demolition, repair, restoration or maintenance of roads and bridges, railways, airports, seaports, communication facilities, civil works components of information technology projects, irrigation, flood control and drainage, water supply, sanitation, sewerage and solid waste management systems, shore protection, energy/power and electrification facilities, national buildings, school buildings, hospital buildings, and other related construction projects of the government. Also referred to as *civil works or works*. (2016 revised IRR, Section 5[u])

LGUs – Local Government Units.

NFCC – Net Financial Contracting Capacity.

NGA – National Government Agency.

PhilGEPS - Philippine Government Electronic Procurement System.

Procurement Project – refers to a specific or identified procurement covering goods, infrastructure project or consulting services. A Procurement Project shall be described, detailed, and scheduled in the Project Procurement Management Plan prepared by the agency which shall be consolidated in the procuring entity's Annual Procurement Plan. (GPPB Circular No. 06-2019 dated 17 July 2019)

PSA – Philippine Statistics Authority.

SEC – Securities and Exchange Commission.

SLCC – Single Largest Completed Contract.

Supplier – refers to a citizen, or any corporate body or commercial company duly organized and registered under the laws where it is established, habitually established in business and engaged in the manufacture or sale of the merchandise or performance of the general services covered by his bid. (Item 3.8 of GPPB Resolution No. 13-2019, dated 23 May 2019). Supplier as used in these Bidding Documents may likewise refer to a distributor, manufacturer, contractor, or consultant.

UN – United Nations.


Notes on the Invitation to Bid

The Invitation to Bid (IB) provides information that enables potential Bidders to decide whether to participate in the procurement at hand. The IB shall be posted in accordance with Section 21.2 of the 2016 revised IRR of RA No. 9184.

Apart from the essential items listed in the Bidding Documents, the IB should also indicate the following:

- a. The date of availability of the Bidding Documents, which shall be from the time the IB is first advertised/posted until the deadline for the submission and receipt of bids;
- b. The place where the Bidding Documents may be acquired or the website where it may be downloaded;
- c. The deadline for the submission and receipt of bids; and
- d. Any important bid evaluation criteria (*e.g.*, the application of a margin of preference in bid evaluation).

The IB should be incorporated in the Bidding Documents. The information contained in the IB must conform to the Bidding Documents and in particular to the relevant information in the Bid Data Sheet.



INVITATION TO BID FOR

WATERWORKS EQUIPMENT ITB-18STF-23

- 1. The *CENTRAL MINDANAO UNIVERSITY*, through the *STF 2023* intends to apply the sum of One Million Three Hundred Sixty Thousand Pesos Only [1,360,000.00] being the ABC to payments under the contract for *Procurement of Waterworks Equipment/ ITB No.-18STF-23]*. Bids received in excess of the ABC per lot shall be automatically rejected at bid opening. Details are as follows:
- 2. The *CENTRAL MINDANAO UNIVERSITY* now invites bids for the above Procurement of Waterworks Equipment. Delivery of the Goods is required within **Three (3) months** upon *receipt of notice to proceed*. Bidders should have completed, within **two (2) years** prior from the date of submission and receipt of bids, a contract similar to the Project. The description of an eligible bidder is contained in the Bidding Documents, particularly, in Section II (Instructions to Bidders).
- 3. Bidding will be conducted through open competitive bidding procedures using a non-discretionary "*pass/fail*" criterion as specified in the 2016 revised Implementing Rules and Regulations (IRR) of Republic Act (RA) No. 9184.

Bidding is restricted to Filipino citizens/sole proprietorships, partnerships, or organizations with at least sixty percent (60%) interest or outstanding capital stock belonging to citizens of the Philippines, and to citizens or organizations of a country the laws or regulations of which grant similar rights or privileges to Filipino citizens, pursuant to RA No. 5183.

- 4. Prospective Bidders may obtain further information from *CENTRAL MINDANAO UNIVERSITY* and inspect the Bidding Documents at the address given below during **7:00-11:00 AM and 1:00-5:00 PM**.
- 5. A complete set of Bidding Documents may be acquired by interested Bidders on May 4, 2023 from the given address and website(s) below *and upon payment of a non-refundable fee of Five Thousand Pesos Only*.

It may also be downloaded free of charge from the website of the Philippine Government Electronic Procurement System (PhilGEPS) and the website of the Procuring Entity. However, the Bidders shall pay the non-refundable fee for the Bidding Documents not later than the submission of their bids.

[NOTE: For lot procurement, the maximum fee for the Bidding Documents for each lot shall be based on its ABC, in accordance with the Guidelines issued by the GPPB; provided that the total fees for the Bidding Documents of all lots shall not exceed the maximum fee prescribed in the Guidelines for the sum of the ABC of all lots.]

6. The *CMU* will hold a Pre-Bid Conference¹ on *May 12, 2023* @ 10:00 AM at BAC Conference Office, CMU, Musuan, Maramag, Bukidnon and/or through video conferencing or webcasting, which shall be open to prospective bidders.

¹ May be deleted in case the ABC is less than One Million Pesos (PhP1, 000,000) where the Procuring Entity may not hold a Pre-Bid Conference.

Bids must be duly received by the BAC Secretariat through manual submission at the office address indicated below, on or before *May 24, 2023 at 10:00 am*. Late bids shall not be accepted.

- 7. All Bids must be accompanied by a bid security in any of the acceptable forms and in the amount stated in **ITB** Clause 14.
- 8. Bid opening shall be on *May 24, 2023 at 10:00 am* at the given address below. Bids will be opened in the presence of the bidders' representatives who choose to attend the activity.
- 9. The *CENTRAL MINDANAO UNIVERSITY* reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract at any time prior to contract award in accordance with Sections 35.6 and 41 of the 2016 revised IRR of RA No. 9184, without thereby incurring any liability to the affected bidder or bidders.
- 10. For further information, please refer to:

IRIS M. DAJAO-OPISO Head, BAC-Secretariat CP# 0917-718-2368 E-mail Add. <u>bac@cmu.edu.ph</u>

11. You may visit the following websites:

For downloading of Bidding Documents: cmu.edu.ph & philgeps.gov.ph

RONEL V. SUDARIA BAC Chairperson for Goods and Services



Republic of the Philippines CENTRAL MINDANAO UNIVERSITY University Town, Musuan, Bukidnon

INSTRUCTION TO BIDDERS

- All bids and eligibility requirements must be submitted to the BAC–Secretariat of Central Mindanao University – Bids and Awards Committee (BAC) on or before 10:00 o'clock in the morning, Central Mindanao University BAC Office time on the day of the scheduled bidding. Bids submitted after the deadline shall not be accepted by the BAC;
- 2. All bids must be accompanied by a Bid Security in an amount equivalent to a percentage of the Approved Budget for the Contract to be bid (ABC) in an acceptable form of bonds as follows:

CASH, MANAGER'S CHECK, CASHIER'S CHECK, BANK DRAFT OR BANK GUARANTEE - 2% OF ABC

SURETY BOND OF ABC - 5%

NOTARIZED BID SECURING DECLARATION

- **3.** The prospective bidder should have an experience in undertaking a similar project within the University or any other government agencies and private companies for the last two (2) years with an amount of at least fifty percent (50 %) of the Approved Budget for the Contract to be bid;
- 4. In case the Net Financial Contracting Capacity (NFCC) is not equal to the ABC prospective bidder must secure a commitment from a License bank to extend to it a credit line if awarded the contract to be bid, or a cash deposit certificate equivalent to at least ten percent (10 %) of the ABC, which is specific to the contract;
- 5. A single-stage, two-envelope system of bidding will be adopted by the BAC;
- 6. A prospective bidder should submit his/her bid documents in two (2) separate sealed bid envelopes, with envelope no. 1 duly mark as Eligibility & Technical requirements, envelope no. 2 mark Financial envelope containing the bid proposal. All envelopes must be sealed in an outer envelope which shall be marked with the name of the contract to be bid and the name of the bidder and addressed to the BAC;
- Bid documents submitted must be in three (3) copies, with the original mark as original copy to facilitate evaluation of the documents by the BAC TWG;

- 8. Eligibility checking of the prospective bidders shall be done using a none discretionary "pass / fail criteria";
- 9. Withdrawal or Modification of Bids after Bid Opening is NOT allowed; Submission of Waiver after Bid Opening will mean forfeiture of Bid Security and Subject to Administrative Sanction Suspension of one year for 1st offense and Suspension of two years for the second offense.
- **10.** All items are subject to inspection and tests prior to acceptance and payment.
- **11.** All representatives shall be authorized by the Owner/ Proprietor through a Special Power of Attorney or a Secretary's Certificate in case of Corporations.
- **12.** All clarifications must be in the form of writing.
- **13.** Attach to make part of this Instruction to Bidders are sample standard forms to be included in the bidding documents.

(Sgd.) RONEL V. SUDARIA BAC Chairman, GOODS AND SERVICES

Section II. Instructions to Bidders

Notes on the Instructions to Bidders

This Section on the Instruction to Bidders (ITB) provides the information necessary for bidders to prepare responsive bids, in accordance with the requirements of the Procuring Entity. It also provides information on bid submission, eligibility check, opening and evaluation of bids, post-qualification, and on the award of contract.

1. Scope of Bid

The Procuring Entity, *CENTRAL MINDANAO UNIVERSITY* wishes to receive Bids for the [*Procurement of Waterworks Equipment*], with identification number [*ITB NO. 18STF-23*].

[Note: The Project Identification Number is assigned by the Procuring Entity based on its own coding scheme and is not the same as the PhilGEPS reference number, which is generated after the posting of the bid opportunity on the PhilGEPS website.]

The Procurement Project (referred to herein as "Procurement of Waterworks Equipment") is composed of [*LOT 1*], the details of which are described in Section VII (Technical Specifications).

2. Funding Information

- 2.1. The GOP through the source of funding as indicated below for [STF 2023] in the amount of (1,360,000.00)
- 2.2. The source of funding is: SPECIAL TRUST FUND

3. Bidding Requirements

The Bidding for the Project shall be governed by all the provisions of RA No. 9184 and its 2016 revised IRR, including its Generic Procurement Manuals and associated policies, rules and regulations as the primary source thereof, while the herein clauses shall serve as the secondary source thereof.

Any amendments made to the IRR and other GPPB issuances shall be applicable only to the ongoing posting, advertisement, or **ITB** by the BAC through the issuance of a supplemental or bid bulletin.

The Bidder, by the act of submitting its Bid, shall be deemed to have verified and accepted the general requirements of this Project, including other factors that may affect the cost, duration and execution or implementation of the contract, project, or work and

examine all instructions, forms, terms, and project requirements in the Bidding Documents.

4. Corrupt, Fraudulent, Collusive, and Coercive Practices

The Procuring Entity, as well as the Bidders and Suppliers, shall observe the highest standard of ethics during the procurement and execution of the contract. They or through an agent shall not engage in corrupt, fraudulent, collusive, coercive, and obstructive practices defined under Annex "I" of the 2016 revised IRR of RA No. 9184 or other integrity violations in competing for the Project.

5. Eligible Bidders

5.1. Only Bids of Bidders found to be legally, technically, and financially capable will be evaluated.

5.2.

- a. Foreign ownership exceeding those allowed under the rules may participate pursuant to:
 - i. When a Treaty or International or Executive Agreement as provided in Section 4 of the RA No. 9184 and its 2016 revised IRR allow foreign bidders to participate;
 - Citizens, corporations, or associations of a country, included in the list issued by the GPPB, the laws or regulations of which grant reciprocal rights or privileges to citizens, corporations, or associations of the Philippines;
 - iii. When the Goods sought to be procured are not available from local suppliers; or
 - iv. When there is a need to prevent situations that defeat competition or restrain trade.
- 5.3. Pursuant to Section 23.4.1.3 of the 2016 revised IRR of RA No.9184, the Bidder shall have an SLCC that is at least one (1) contract similar to the Project the value of which, adjusted to current prices using the PSA's CPI, must be at least equivalent to:

- a. For the procurement of Expendable Supplies: The Bidder must have completed a single contract that is similar to this Project, equivalent to at least twenty-five percent (25%) of the ABC.
- 5.4. The Bidders shall comply with the eligibility criteria under Section 23.4.1 of the 2016 IRR of RA No. 9184.

6. Origin of Goods

There is no restriction on the origin of goods other than those prohibited by a decision of the UN Security Council taken under Chapter VII of the Charter of the UN, subject to Domestic Preference requirements under **ITB** Clause 18.

7. Subcontracts

7.1. The Bidder may subcontract portions of the Project to the extent allowed by the Procuring Entity as stated herein, but in no case more than twenty percent (20%) of the Project.

The Procuring Entity has prescribed that:

- a. Subcontracting is allowed. The portions of Project and the maximum percentage allowed to be subcontracted are indicated in the **BDS**, which shall not exceed twenty percent (20%) of the contracted Goods.
- 7.2. [If Procuring Entity has determined that subcontracting is allowed during the bidding, state:] The Bidder must submit together with its Bid the documentary requirements of the subcontractor(s) complying with the eligibility criteria stated in **ITB** Clause 5 in accordance with Section 23.4 of the 2016 revised IRR of RA No. 9184 pursuant to Section 23.1 thereof.
- 7.3. [If subcontracting is allowed during the contract implementation stage, state:] The Supplier may identify its subcontractor during the contract implementation stage. Subcontractors identified during the bidding may be changed during the implementation of this Contract. Subcontractors must submit the documentary requirements under Section 23.1 of the 2016 revised IRR of RA No. 9184 and comply with the eligibility criteria specified in **ITB** Clause 5 to the implementing or end-user unit.
- 7.4. Subcontracting of any portion of the Project does not relieve the Supplier of any liability or obligation under the Contract. The Supplier will be responsible for the acts, defaults, and negligence of any subcontractor, its agents, servants, or workmen as fully as if these were the Supplier's own acts, defaults, or negligence, or those of its agents, servants, or workmen.

8. Pre-Bid Conference

The Procuring Entity will hold a pre-bid conference for this Project on the specified date and time and either at its physical address {*[insert if applicable]* and/or through videoconferencing/webcasting} as indicated in paragraph 6 of the **IB**.

9. Clarification and Amendment of Bidding Documents

Prospective bidders may request for clarification on and/or interpretation of any part of the Bidding Documents. Such requests must be in writing and received by the Procuring Entity, either at its given address or through electronic mail indicated in the **IB**, at least ten (10) calendar days before the deadline set for the submission and receipt of Bids.

10. Documents comprising the Bid: Eligibility and Technical Components

- 10.1. The first envelope shall contain the eligibility and technical documents of the Bid as specified in Section VIII (Checklist of Technical and Financial Documents).
- 10.2. The Bidder's SLCC as indicated in **ITB** Clause 5.3 should have been completed within *[state relevant period as provided in paragraph 2 of the IB]* prior to the deadline for the submission and receipt of bids.
- 10.3. If the eligibility requirements or statements, the bids, and all other documents for submission to the BAC are in foreign language other than English, it must be accompanied by a translation in English, which shall be authenticated by the appropriate Philippine foreign service establishment, post, or the equivalent office having jurisdiction over the foreign bidder's affairs in the Philippines. Similar to the required authentication above, for Contracting Parties to the Apostille Convention, only the translated documents shall be authenticated through an apostille pursuant to GPPB Resolution No. 13-2019 dated 23 May 2019. The English translation shall govern, for purposes of interpretation of the bid.

11. Documents comprising the Bid: Financial Component

- 11.1. The second bid envelope shall contain the financial documents for the Bid as specified in Section VIII (Checklist of Technical and Financial Documents).
- 11.2. If the Bidder claims preference as a Domestic Bidder or Domestic Entity, a certification issued by DTI shall be provided by the Bidder in accordance with Section 43.1.3 of the 2016 revised IRR of RA No. 9184.
- 11.3. Any bid exceeding the ABC indicated in paragraph 1 of the **IB** shall not be accepted.

- 11.4. For Foreign-funded Procurement, a ceiling may be applied to bid prices provided the conditions are met under Section 31.2 of the 2016 revised IRR of RA No. 9184.
- 11.5. *[Include if Framework Agreement will be used:]* Financial proposals for single or multi-year Framework Agreement shall be submitted before the deadline of submission of bids as prescribed in the **IB**. For multi-year Framework Agreement, evaluation of the financial proposal during this stage is for purposes of determining eligibility and whether or not such financial proposal is within the ABC.

12. Bid Prices

- 12.1. Prices indicated on the Price Schedule shall be entered separately in the following manner:
 - a. For Goods offered from within the Procuring Entity's country:
 - i. The price of the Goods quoted EXW (ex-works, ex-factory, exwarehouse, ex-showroom, or off-the-shelf, as applicable);
 - ii. The cost of all customs duties and sales and other taxes already paid or payable;
 - iii. The cost of transportation, insurance, and other costs incidental to delivery of the Goods to their final destination; and
 - iv. The price of other (incidental) services, if any, listed in e.
 - b. For Goods offered from abroad:
 - i. Unless otherwise stated in the **BDS**, the price of the Goods shall be quoted delivered duty paid (DDP) with the place of destination in the Philippines as specified in the **BDS**. In quoting the price, the Bidder shall be free to use transportation through carriers registered in any eligible country. Similarly, the Bidder may obtain insurance services from any eligible source country.
 - ii. The price of other (incidental) services, if any, as listed in Section VII (Technical Specifications).
- 12.2. *[Include if Framework Agreement will be used:]* For Framework Agreement, the following should also apply in addition to Clause 12.1:
 - a. For a single year Framework Agreement, the prices quoted by the Bidder shall be fixed during the Bidder's performance of the contract and not subject to variation or escalation on any account. Price schedules required under Clause 12.1 shall be submitted with the bidding documents.
 - b. For a multi-year Framework Agreement, the prices quoted by the Bidder during submission of eligibility documents shall be the ceiling and the price quoted during mini-competition must not exceed the initial price offer. The

price quoted during call for mini-competition shall be fixed during the Bidder's performance of that Call-off and not subject to variation or escalation on any account. Price schedules required under Clause 12.1 shall be submitted with the bidding documents.

13. Bid and Payment Currencies

- 13.1. For Goods that the Bidder will supply from outside the Philippines, the bid prices may be quoted in the local currency or tradeable currency accepted by the BSP at the discretion of the Bidder. However, for purposes of bid evaluation, Bids denominated in foreign currencies, shall be converted to Philippine currency based on the exchange rate as published in the BSP reference rate bulletin on the day of the bid opening.
- 13.2. Payment of the contract price shall be made in:
 - a. Philippine Pesos.

14. Bid Security

- 14.1. The Bidder shall submit a Bid Securing Declaration² or any form of Bid Security in the amount indicated in the **BDS**, which shall be not less than the percentage of the ABC in accordance with the schedule in the **BDS**.
- 14.2. The Bid and bid security shall be valid until shall exceed one hundred twenty (120) calendar days from the date of the opening of bids. Any Bid not accompanied by an acceptable bid security shall be rejected by the Procuring Entity as non-responsive.

15. Sealing and Marking of Bids

Each Bidder shall submit one copy of the first and second components of its Bid.

The Procuring Entity may request additional hard copies and/or electronic copies of the Bid. However, failure of the Bidders to comply with the said request shall not be a ground for disqualification.

If the Procuring Entity allows the submission of bids through online submission or any other electronic means, the Bidder shall submit an electronic copy of its Bid, which must be digitally signed. An electronic copy that cannot be opened or is corrupted shall be considered non-responsive and, thus, automatically disqualified.

 $^{^{2}}$ In the case of Framework Agreement, the undertaking shall refer to entering into contract with the Procuring Entity and furnishing of the performance security or the performance securing declaration within ten (10) calendar days from receipt of Notice to Execute Framework Agreement.

16. Deadline for Submission of Bids

- 16.1. The Bidders shall submit on the specified date and time and either at its physical address or through online submission as indicated in paragraph 7 of the **IB**.
- 16.2. *[Include if Framework Agreement will be used:] For* multi-year Framework Agreement, the submission of bids shall be for the initial evaluation of their technical and financial eligibility. Thereafter, those declared eligible during the said initial eligibility evaluation and entered into a Framework Agreement with the Procuring Entity shall submit anew their best financial offer at the address and on or before the date and time indicated in the Call for each mini-competition.

17. Opening and Preliminary Examination of Bids

17.1. The BAC shall open the Bids in public at the time, on the date, and at the place specified in paragraph 9 of the **IB**. The Bidders' representatives who are present shall sign a register evidencing their attendance. In case videoconferencing, webcasting or other similar technologies will be used, attendance of participants shall likewise be recorded by the BAC Secretariat.

In case the Bids cannot be opened as scheduled due to justifiable reasons, the rescheduling requirements under Section 29 of the 2016 revised IRR of RA No. 9184 shall prevail.

17.2. The preliminary examination of bids shall be governed by Section 30 of the 2016 revised IRR of RA No. 9184.

18. Domestic Preference

- 18.1. The Procuring Entity will grant a margin of preference for the purpose of comparison of Bids in accordance with Section 43.1.2 of the 2016 revised IRR of RA No. 9184.
- 18.2. *[Include if Framework Agreement will be used:] For* multi-year Framework Agreement, determination of margin of preference shall be conducted every call for Mini-Competition.

19. Detailed Evaluation and Comparison of Bids

19.1. The Procuring BAC shall immediately conduct a detailed evaluation of all Bids rated "*passed*," using non-discretionary pass/fail criteria. The BAC shall consider the conditions in the evaluation of Bids under Section 32.2 of the 2016 revised IRR of RA No. 9184.

[Include the following options if Framework Agreement will be used:]

a. In the case of single-year Framework Agreement, the Lowest Calculated Bid shall be determined outright after the detailed evaluation;

- b. For multi-year Framework Agreement, the determination of the eligibility and the compliance of bidders with the technical and financial aspects of the projects shall be initially made by the BAC, in accordance with Item 7.4.2 of the Guidelines on the Use of Framework Agreement.
- 19.2. If the Project allows partial bids, bidders may submit a proposal on any of the lots or items, and evaluation will be undertaken on a per lot or item basis, as the case maybe. In this case, the Bid Security as required by **ITB** Clause 15 shall be submitted for each lot or item separately.
- 19.3. The descriptions of the lots or items shall be indicated in Section VII (Technical Specifications), although the ABCs of these lots or items are indicated in the BDS for purposes of the NFCC computation pursuant to Section 23.4.2.6 of the 2016 revised IRR of RA No. 9184. The NFCC must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder.
- 19.4. The Project shall be awarded as follows:

Option 2 – One Project having several items grouped into several lots, which shall be awarded as separate contracts per lot.

19.5. Except for bidders submitting a committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation, all Bids must include the NFCC computation pursuant to Section 23.4.1.4 of the 2016 revised IRR of RA No. 9184, which must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder. For bidders submitting the committed Line of Credit, it must be at least equal to ten percent (10%) of the ABCs for all the lots or items participated in by the prospective Bidder.

20. Post-Qualification

- 20.1. [Include if Framework Agreement will be used:] For multi-year Framework Agreement, all bidders initially determined to be eligible and financially compliant shall be subject to initial post-qualification. The BAC shall then recommend the execution of a Framework Agreement among all eligible, technically and financially compliant bidders and the Procuring Entity and shall be issued by HoPE a Notice to Execute Framework Agreement. The determination of the Lowest Calculated Bid (LCB) shall not be performed by the BAC until a Mini-Competition is conducted among the bidders who executed a Framework Agreement. When a Call for Mini-Competition is made, the BAC shall allow the bidders to submit their best financial proposals on such pre-scheduled date, time and place to determine the bidder with the LCB.
- 20.2. Within a non-extendable period of five (5) calendar days from receipt by the Bidder of the notice from the BAC that it submitted the Lowest Calculated Bid, {[Include if Framework Agreement will be used:] or in the case of multi-year Framework Agreement, that it is one of the eligible bidders who have submitted bids that are found to be technically and financially compliant,}the Bidder shall

submit its latest income and business tax returns filed and paid through the BIR Electronic Filing and Payment System (eFPS) and other appropriate licenses and permits required by law and stated in the **BDS**. {*[Include if Framework Agreement will be used:]* For every mini-competition in Framework Agreement, the LCB shall likewise submit the required documents for final Post Qualification.}

21. Signing of the Contract

- 21.1. The documents required in Section 37.2 of the 2016 revised IRR of RA No. 9184 shall form part of the Contract. Additional Contract documents are indicated in the **BDS**.
- 21.2. At the same time as the Procuring Entity notifies the successful Bidder that its bid has been accepted, the Procuring Entity shall send the Framework Agreement Form to the Bidder, which contract has been provided in the Bidding Documents, incorporating therein all agreements between the parties.
- 21.3. Within ten (10) calendar days from receipt of the Notice to Execute Framework Agreement with the Procuring Entity, the successful Bidder or its duly authorized representative shall formally enter into a Framework Agreement with the procuring entity for an amount of One Peso to be paid to the procuring entity as a consideration for the option granted by the procuring entity to procure the items in the Framework Agreement List when the need arises.
- 21.4. The Procuring Entity shall enter into a Framework Agreement with the successful Bidder within the same ten (10) calendar day period provided that all the documentary requirements are complied with.
- 21.5. The following documents shall form part of the Framework Agreement:
 - a. Framework Agreement Form;
 - b. Bidding Documents;
 - c. Call-offs;
 - d. Winning bidder's bid, including the Technical and Financial Proposals, and all other documents/statements submitted (*e.g.*, bidder's response to request for clarifications on the bid), including corrections to the bid, if any, resulting from the Procuring Entity's bid evaluation;
 - e. Performance Security or Performance Securing Declaration, as the case may be;
 - f. Notice to Execute Framework Agreement; and
 - g. Other contract documents that may be required by existing laws and/or specified in the **BDS**.

Section III. Bid Data Sheet

Notes on the Bid Data Sheet

The Bid Data Sheet (BDS) consists of provisions that supplement, amend, or specify in detail, information, or requirements included in the ITB found in Section II, which are specific to each procurement.

This Section is intended to assist the Procuring Entity in providing the specific information in relation to corresponding clauses in the ITB and has to be prepared for each specific procurement.

The Procuring Entity should specify in the BDS information and requirements specific to the circumstances of the Procuring Entity, the processing of the procurement, and the bid evaluation criteria that will apply to the Bids. In preparing the BDS, the following aspects should be checked:

- a. Information that specifies and complements provisions of the ITB must be incorporated.
- b. Amendments and/or supplements, if any, to provisions of the ITB as necessitated by the circumstances of the specific procurement, must also be incorporated.

Bid Data Sheet

Clause 5.3	T .1.1				
	For this	purpose, contracts similar to the Project	et shall be:		
	a. [Procurement of Waterworks Equipmen	nt].		
		Completed within [2 YEARS] prior to t eceipt of bids.	he deadline	for the su	ubmission and
7.1		the portions of Goods to be subcontrac ial component of the Project as detern			0 1
12	The pric	e of the Goods shall be quoted DDP le International Commercial Terms (IN	[state place	e of desti	nation] or the
14.1		security shall be in the form of a Bid s g forms and amounts:	Securing De	eclaration	, or any of the
	t	The amount of not less than 27,200.00 wo percent (2%) of ABC], if bid securitheck, bank draft/guarantee or irrevoca	rity is in ca	sh, cashie	er's/manager's
		The amount of not less than 68,000.00 <i>ive percent</i> (5%) of ABC] if bid securit			t equivalent to
19.3	the grou	the Project will be awarded by lot, lis up title, items, and the quantity fo nding ABC for each item.]	• •		
	ITEM NO.	DESCRIPTION	UNIT	QTY	UNIT COST
		GOODS:			
	R.Agui lar				
		150mm MECHANICAL FLOW METER meter size: 150mm nominal diameter maximum rated capacity Qmax: Qmax \geq 600m3/hour nominal capacity for continued duty Qn: Qn \geq 450m3/hour transitional flow Qt: Qt \leq 4m3/hour minimum flow rate Qt: ¹ Qmin \leq 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 600 m3/h allowable error \pm 2% Qn 450m3/h allowable error \pm 2% Qmin 1.8m3/h allowable error \pm 5% maximum reading: 10,000,000 m3 smallest reading: 0.005m3	unit	2	260,000.00

	register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading Pulser Specifications: Simple installation, pulser can be fitted without breaking the meter seal, two different pulse values, protection rating: IP68, temperature range: Up 50°C Online Data Logger Programming and downloading: via Bluetooth Data viewing: via web portal (unlimited user access) antenna: external Analogue/pressure: internal pressure transducer, accuracy ± 0.1% of full range, quick release male connection, pressure range of 0-20 bar or higher Digital/flow: bi-directional/option to combine into single log value, max pulse frequency: 1000Hz, switches to event pulse interval timing at low pulse rates Recording travel: at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body: extruded 6063 aluminum protection classification: IP 68-fully submersible in depth of 1m, power supply: battery operated, minimum operation of 5 years under normal operating conditions web server:			
	signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow)			
2	100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Q max \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour minimum flow rate Qt:' Qmin \leq 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qn 230m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qmin 0.8m3/h allowable error \pm 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat \geq 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt	units	4	210,000.00

Instruction prior for pressure sensors Meter Accessories: 1. Pulser/Read swith 3-motor lingth wire open ended 2. Stanless skel bolts & pieces for fange end PN16 3. meter fange gadets 2. Stanless skel bolts & pieces for fange end PN16 3. meter fange gadets 2. Stanless skel bolts & pieces for fange end PN16 3. meter fange gadets 2. Stanless skel bolts & pieces can be fitted without threaking the meter skel, bod different puise values, 0. Office Data Logger Programming end downloading: via Bluetooth Data velowing: via web portal (unlimited user access) anterna: stornal Analoguapressure: Internal pressure fangetoring tavel 0. Bits of full mage, quick relates mice connection, pressure mange 0.0.20 bits or higher DigitalTMCs bid for compare matalara body: manor, at least 4gb of memory matalara body: motal for f	 	 •	
Meter Accessories: 1. Pulser/Red switch sensor with 3-meter length wire open ended 2. stainless stal bots 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading Pulse SopeCinctions: Simple installation, pulser can be fitted without breaking the meter seal, two different pulses values, protection rating: IP68, temperature range: Up SUPC Online Data Logger Programming and downloading: via Blautoch Data verying: via web portal (infimide user access) anterna: external 3. The fitted infinite into single log value, max pubs flaquency: 100Hz, switches to avent patientificary: building on pubsis ratios Reaconing travit at least capable or in pubsis ratios Reaconing travit at least capable or in pubsis ratios Reaconing travit at least capable and reacting travits and server operation continuum protection dosalization: IP 68- folly building solution for water and pubsis ratios Reaconing travit at least capable in comprometable in dog for persisted. minimum protection dosalization: IP 68- folly building solution for water and pubsis ratios Reaconing travit at least capable in comprometable in dog for the logger conditions web server: capable to daging data in chart form, table form, daily summary and afarms dout based an antiprice analytone capable of detecting logger position in poole maps the logger wind alarms confluction and servers anarphone capable of addetional requirements (to be submitted during operating compation in poole maps the logger mats be capable to that to webserver or perferred this pathole and pubsic pathole of catalogtbrochure of the logger to samatphone of tablet, request of installation and commissioning the koger in dinstallation and commissioning or catalogtbrochure of the data l			
I. Pulse-Reed switch sensor with 3-meter length wire open ended 2. Stainless stell bolts 8 pieces for flange end PN16 3. meter lange gastes 10 (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	 		
2. stainless stell bolts & pieces for flange end PN16 3. meter image gastell 4. The image gastell 10 and the image gastelline image gastelline image gastelline image gastell			
3. meter fange gaskes: Puise Output Connectivity: Puise Output Connectivity: The meter shall have puise output connectivity for data loging or remote reading Puiser Specifications: Simple netabilition, puiser can be fitted without breaking the meter seal, two different puise values, protection rating. IPS8, thereafture range: Up 50°C Online Data Logger Pogramming and downloading: via Bluetooth Data viewing via web portal (unlimited user access) antenna: netamal Anatogue pressure: Internal pressure transducer, accuracy a. 0.1% of full range, spuck release mele connection, pressure range of 0.2 box or higher Digitalifion: b-directionsiloption to comtaine into single log value, max puise forecording in 1 second up to 24 hours interva: allest dip of memory material body: extuded 0603 alumnum protection dessification: IP 68- luity submersible in depth of Im, power supply battery operated. Viab dip of memory material body: extraded 0603 alumnum protection dessification: IP 68- luity submersible in depth of Im, power supply battery operated. or logger most the orabit on of Sysars under normal operating conditions web server: capable to dipaly data In chart form, table form, daily summary and alarms dout base-disruptice solution for water network pressure and flow via browser table to rismarphone capable of detecting logger position in googe maps the logger must be capable bid not limited to the ff: signal sergint hest, scycing, sum submit an original colory or attable, prediction dissistion or positive subply operated. We apply and installation and commissioning Additional requirements (to be submitted during opering of the logger via stant an original color) or data largerise, sum submit an original color or data largerise, submitted during opering of the solutions (to meak originate on pof dialoginger position (sor gasering data colored fore originge			
Pulse Output Connectivity for data loging or remote reading Pulser Specifications: Simple installation, pulser can be fitted without breaking the meter scale, how officered tables values; protection rating; IP68, temperature range: Up 50°C Online Data Logger Programming and downloading: via Bluetooth Data Verving: via web portici (unlined user access) antenna: external Analogue/prossure: internal pressure transducer, accuracy = 0.1% of 111 range, quick relases male connection, pressure range of 0.20 ber or higher Digital/Discription to combine into single log value, max pulse frequency: 1000Hz, switches to event pulse interval timing at two pulse rates Recording tavel: at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body: extruded 6053 aluminum protection dissification: IP 68- tully subminum operation of systems under normal operating conditions: web server: capable to display data in chart form, daily summary and alarms doub based-antifycis solution for water network pressure and flow with browser tables of recording tavels in the logger most to expected to an subchene capable of detecting logger position in google maps the logger most to expected to the cover form web portal, caser to use free antiou application and seture of the logger sistemation and or display data in chart form web portal, caser to use free antiou application and seture of the logger to preferred third party data hosting platform minimum nequired number and your data to velower or preferred third party data hosting platform minimum requirements (to be esubmitted during operating the security data hosting platform minimum requirements (to the assert, 2 damnets (fx internal pressure, 1 digital flow) <td></td> <td></td> <td></td>			
logging or emote reading Pulser's pediction; pulser can be filted without breaking the meder seal, two different pulse values, protection rating; IP68, temperature range: Up 60°C Online Data Logger Programming and downloading: via Bluetooth Data viewing: via veb potch (unlined user access) anterna: external Anatogue/pressure: internal pressure transducer, accuracy; ±.0.1% of Ull range, quick release male connection, pressure range of 0.20 bar or higher Digita/Div bi-directionalogiton to combine into single log value, max pulse frequency: 1000Hz, switches to avent pulse interval iming at low pulse rates Recording travel: at least dgb of memory material body: extruded 6063 aluminum protection dassification: IP 68- fully submerable in depked or fram, bore supply, battery operating onditions web server: operating onditions web server: operating ond supplication allows simple writeless conditional requirements (da ba polication allow simple writeless odd wite bowset bial to assolid and low webserver or operating of instantaneous data veixing via aup, with He system that can send your data to webserver or operating of instantaneous data veixing via aup, with He system that can send your data to webserver or prefered third party data hesting platform <td></td> <td></td> <td></td>			
Pulse "Specifications: Simple installation, pulser can be fitted without breaking the meler seal, two different pulse values, protection rating: IP68, temperature range: Up 50°C Online Data Logger Programming and downloading: via Bluetooth Data verying: via web point (unifinited user access) anterna: external Analoguéressue: internal pressure transducer, accuracy ± 0.1% of tul range, guick release male connection, pressure range of 0.20 bor or higher Digital*flow: bi-directionalopton to combine into single log value, max pulse frequency: 1000/L2, switches to event pulse interval timing at tow pulse rates Rescalation: IP 88-filling at the second provide rates Rescalator. IP 88-filling automorphic protection dassification: IP 88-filling automorphic bio server: capable to display data in chart form, table form, daily summary and alarms: chould based-analytics solution for water network pressure and fow via browser table or smartphone capable of detecting logger russ to capable but not limited to the ff: signal strength test, export data to excell form web portal, easy to use free android application allows; wia app, with API system that can send your data to websarver or preferred third application allows; wia app, with API system that can send your data to websarver or preferred third apply data flows) configuration and serves 1. digital flow) viath and pressure, 1. digital flow) viath apply and installation and commissioning Additional requirements (to be submitted during opering of bidd) pelvery periori			
Simple installation, pulser can be fitted without breaking the meter seal, two different pulse values, protection rating: IP68, temperature range: Up 50°C Online Data Logger Programming and downloading: via Bluetooth Data viewing: via web potal (unlimited user access) anterna: external Anatogue/pressure: internal pressure transducer, accuracy 4.0 1% of MI range, quick release male connection, pressure range of 0.20 bar or higher Digital/Mov bi-directionoliciption to combine into single log value. max pulse frequency: 1000Hz, switches to event pulse interval imming at low pulse rates Recording travel: at least capable of recording in 1 second up to 2 hours interval interval operating conditions web server: capable of direction of System under normal operating conditions web server: capable of direction of system under normal operating conditions web server: capable of direction also web server: capable of display data in chart form, table form, daily summary and alerms cloud based-analytics solution for water network pressure and diverse based bat not limited to the ff. signal strangth test, export data to web server or prejert with supply and installation and commissioning Additional requirements (to be submitted during opering of bids) palevery perior: 30days, must submit an original copy of catalogrochure of the data logger manual, must incide a necesars			
protection rating: IPB6, temperature range: Up 50°C Online Data Logger Programming and downloading: via Bluetooth Data wiening: via web portal (unlimited user accurse) ± 0.1% of full range, uplick release mate connection, pressure range of 0-20 bar or higher Digitalifox: b-directoral/option to combine into single log value, max public frequency: 100Hz, switches to event public interval timing at low public rates Recording travel: at lease capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body: extunded 6063 aluminum protection classification: IP 68- fully submersible in depth of Tim, power supply, battery operating conditions web server: capable to display data in chart form, table form, daily summary and alarms doub dased analytics solution for water network pressure and flow via browser tablet or smartphone capable of detecting logger position in googie maps the logger must be capable but not limited to the ff. signal strength test, export data to seckiny via smartphone of tabler, request of instanteneous data viewing via app, with API system that can send your data to webserver or preferred trind party data hosting jatform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) Delivery perinid: 30days, must submit an original copy of			
Online Data Logger Programming and downloading: via Bluetooth Data viewing: via web portal (unlimited user access) antenzi: external Analogue/pressure: internal pressure transducer, accuracy ± 0.1% of full range, quick release male connection, pressure range of 0.20 bar o higher Digitatifice: i-directional/option to combine into single log value, max pulse frequency: 1000Hz, switches to event pulse: interval iming at low gulse rates Recording travel: at least capable of recording in 1 second up to 24 hours interval interval operating conditions web server: capable to display data in chart form, table form, daily summary and alarms dud based-analytics solution for web relever: capable to display data in chart form, table form, daily summary and alarms dud based-analytics solution for web relever: capable to display data in chart form, table form, daily summary and alarms dud based-analytics solution for web relever: capable to display data in chart form, daily summary and alarms summary and alarms und based analytics solution to invider network presure and flow via browear tablet o			
Programming and downloading: via Bluetooth Data viewing: via web portal (unlimited user accurse): analogue/pressure: internal pressure transducer, accuracy: ± 0.1% of full range, quick relases male connection, pressure range of 0-20 bar or higher Digital/flow: bi-directional/option to combine into single log value, max puble frequency: 1000Hz, switches to event puble interval timing at low puble rates Recording travel: at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body: extrude 0063 attimium protection dassistication: IP 68- fully submersible in depth of 1m, power supply: battery operating conditions web server: capable to disptay data in chart form, table form, daly summary and alarms: cloud based-analytics solution for water network pressure and flow via browser table or smartphone capable of detecting logger position in google maps the logger must ho experive insmartphone of table, request of instantaneous data viewing via app, with Arbowser table or smartphone of table, request of instantaneous data viewing via app, with Parystern that can send your data to vebaserior or preferred tri			
Data viewing: via web portal (ultimited user access) antenna: external Analogue/pressure: internal pressure transducer, accuracy = 0.1% of full range, quick release male connection, pressure range of C.2 bar or higher Digitalifox: b-directional/option to combine into single log value, max pulse frequency: 1000Hz, switches to event pulse interval liming at to pulse rates Recording travel: at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body: extruded 6063 aluminum protection classification: IP 68- fully submersible in dept of 1m. power supply: battery operated, minimum operation of 5 years under normal operating conditions web server: capable to display data in chart form, table form, daily summary and alarms dout based-analytics solution for water network pressure and flow via borwser table or smartphone capable of detecting logger position in google maps the logger must be capable to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of table, request of instantaneous data viewing via app, with AP system that can send your data to websarver or preferred tring and y data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning poning of based number of hannels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation could be of data logger manual, must include necessary fitting for each logger (Compliance upon delivery). SIM Card inclusive of 1 year load for data transmissing (compliance upon delivery), supplier must have Manufacturer's Authorization Cartificate specific for this project, Supplier should have ISO S0012015 Certificates. Warranty (Complian			
Analogue/pressure: internal pressure transducer, accuracy ± 0.1% of full range, quick release male connection, pressure range of 0-20 bar or higher Digital/tow: b-directional/option to combine into single log value, max pulse frequency: 1000+tz, switches to event pulse interval timing at low pulse rates Recording travel: at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body: extruded 6005 aluminum protection classification. IP 68- fully submersible in depth of Im, power supply: battery operated, minimum operation of 5 years under normal operating conditions web server: capable to display data in chart form, table form, daily summary and alarms cloud based-analytics solution for water network pressure and flow via browser tableto rs martphone capable of detecting logger proteinin ig oogle maps the logger must be capable but not limited to the ff. signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via agn, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opering of bids) Delivery, period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary flowings for each logger (Compliance upon delivery), Simplers found have load for data transmision (compliance upon delivery), supplier must have Manufacturer's	Data viewing: via web portal (unlimited user access)		
 ± 0.1% of full range, quick release male connection, pressure range of 2-0 bar or higher Digital/flow: bi-directional/option to combine into single log value, max pulse frequency: 100Hz, switches to event pulse interval timing at low pulse rates Recording travel: at least capable of ecording in 1 second up to 24 hours interval memory: at least 4gb of memory material body; extruded 6063 atuminum protection classification: IP 68-fully submersible in depth of 1m, power supply, battery operating conditions web server: capable to display data in chart form, table form, daily summary and alarms cloud based-analytics solution for water network pressure and flow via browser tablet or smatphone capable of detecting logger position in googie maps the logger must be capable but netwing via app, with API system that an early our data to weberver or prefered thrid party data indexing partial moves data viewing via app, with API system that, an early our data to weberver or prefered thrid party data indexing platform minimism required number of channels: 2 channels (1x internal pressure, 1 digital flow) 			
pressure range of 2-20 bar or higher Digital/flow: b-directional/option to combine into single log value; max pulse frequency: 1000Hz, switches to event pulse interval timing at low pulse rates Recording travel: at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body: extrude 60603 alumitum operation of 3 system under normal operated, minimum operation of 5 years under normal operated, minimum operation of system under normal operated, minimum operation for water network pressure and flow via browser tablet or smartphone capable of deuter logger possibilin in google maps the logger must be capable but not limited to the ff. signal strength heat; export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data wiewing via app, with API system that can send your data to webserver or prefered third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted			
value, max pulse frequency: 1000Hz, switches to event pulse interval timing at tow pulse rates Recording travel: at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body: extruded 6063 aluminum protection classification: IP 68- fully submersible in depth of fm, power supply: battery operating conditions web server: capable to disply data in chart form, table form, daily summary and alarms cdoud based-analytics solution for water network pressure and flow via browser table to smartphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff: signal strength test, export data to excel form web portal, eases, you can fore android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantareous data viewing via app, with API system that can send your data to webserver or prefered third party data hosting platform mimum required momber of tablet, requirements (to be submitted during opening of bids) Delivery period: 30days, must submit an original copy of cataloghrochure of the data logger, must submit an original copy of cataloghrochure of the data logger, must submit an original copy of cataloghrochure of the data logger, must submit an original cocpy of cataloghrochure of the data logger, manual, must	pressure range of 0-20 bar or higher		
max pulse frequency: 1000Hz, switches to event pulse interval timing at low pulse rates Recording travel: at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body: extruded 6063 atuminum protection classification: IP 68- fully submersible in depth of 1m, power supply: battery operated, minimum operation of 5 years under normal operating conditions web server: capable to display data in chart form, table form, daily summary and alarms cbud based-analytics solution for water network pressure and flow via browser table to smartphone capable of detecting logger position in google maps the logger must be capable but the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project. Supplies for append of one (1) year flom			
pulse interval timing at two pulse rates Recording travel: at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body: extruded 6063 atuminum opteetion classification: IP 68- fully submersible in depth of 1m, power supply: battery operating conditions web server: capable to display data in chart form, table form, daily summary and atams cloud based-analytics solution for water network pressure and flow via browser tablet or smartphone capable of detecting logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of bids) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplie should have ISO 901:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of ne (1) year from			
at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body: extruded 6063 aluminum protection classification: IP 68- fully submersible in depth of 1m, power supply: battery operated, minimum operation of 5 years under normal operating conditions web server: capable to display data in chart form, table form, daily summary and alarms cloud based-analytics solution for water network pressure and flow via browser table to smartphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff: signal strength test, export data to excel form web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosing platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning opening of model and logger, must submit an original copy of catalog/brochure of the data logger, must submit original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), Supplier must have Manufacturer's Authorization Certificate specific for this project, Supplies should have ISO 901:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of ne (1) year from			
memory: at least 4gb of memory material body: extruded 6063 aluminum protection classification: IP 68- fully submersible in depth of 1m, power supply: battery operated, minimum operation of 5 years under normal operating conditions web server: capable to display data in chart form, table form, daily summary and alarms cloud based-analytics solution for water network pressure and flow via browser table to remarphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via samtchhone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred thrid party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of bids) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery). SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shal be guaranteed against defects in workmanship and materials for a period of one (1) year from	at least capable of recording in 1 second up to 24 hours		
extruded 6063 aluminum protection classification: IP 68- fully submersible in depth of 1m, power supply: battery operated, minimum operation of 5 years under normal operating conditions web server: capable to display data in chart form, table form, daily summary and alarms doud based-analytics solution for water network pressure and flow via browser tablet or smartphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of bids) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
operated, minimum operation of 5 years under normal operating conditions web server: capable to display data in chart form, table form, daily summary and alarms cloud based-analytics solution for water network pressure and flow via browser table to reapable of detecting logger position in google maps the logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of belivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacture			
operating conditions web server: capable to display data in chart form, table form, daily summary and alarms cloud based-analytics solution for water network pressure and flow via browser tablet or smartphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening bids) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery); supplier must have Manufacturer's Authorization Certificate			
capable to display data in chart form, table form, daily summary and alarms cloud based-analytics solution for water network pressure and flow via browser tablet or smartphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of belowyre period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have			
summary and alarms cloud based-analytics solution for water network pressure and flow via browser tablet or smarphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smarphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of bids) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original copy of catalog/brochure of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplie			
and flow via browser tablet or smartphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of bids) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon Iso 1001:2015 Certificates, for a per	summary and alarms		
detecting logger position in google maps the logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of bids) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery) supplier supplier should have lSO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of on (1) year from			
the logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of bilds) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of bids) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from	the logger must be capable but not limited to the ff:		
configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of bids) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SlM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery); all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of bids) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of bids) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of bids) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
(1x internal pressure, 1 digital flow) NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of bids) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
Additional requirements (to be submitted during opening of bids)Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
Additional requirements (to be submitted during opening of bids)Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
Additional requirements (to be submitted during opening of bids)Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
Additional requirements (to be submitted during opening of bids)Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
openingofbids)Delivery period:30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from	of catalog/brochure of the data logger, must submit an		
(Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from	load for data transmission (compliance upon delivery),		
ISO 9001:2015 Certificates, Warranty (Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from			
workmanship and materials for a period of one (1) year from			
the date of acceptance	workmanship and materials for a period of one (1) year from		
	the date of acceptance		

20.2	[List here any licenses and permits relevant to the Project and the corresponding law requiring it.]
21.2	[List here any additional contract documents relevant to the Project that may be required by existing laws and/or the Procuring Entity.]

Section IV. General Conditions of Contract

Notes on the General Conditions of Contract

The General Conditions of Contract (GCC) in this Section, read in conjunction with the Special Conditions of Contract in Section V and other documents listed therein, should be a complete document expressing all the rights and obligations of the parties.

Matters governing performance of the Supplier, payments under the contract, or matters affecting the risks, rights, and obligations of the parties under the contract are included in the GCC and Special Conditions of Contract.

Any complementary information, which may be needed, shall be introduced only through the Special Conditions of Contract.

1. Scope of Contract

This Contract shall include all such items, although not specifically mentioned, that can be reasonably inferred as being required for its completion as if such items were expressly mentioned herein. All the provisions of RA No. 9184 and its 2016 revised IRR, including the Generic Procurement Manual, and associated issuances, constitute the primary source for the terms and conditions of the Contract, and thus, applicable in contract implementation. Herein clauses shall serve as the secondary source for the terms and conditions of the Contract.

This is without prejudice to Sections 74.1 and 74.2 of the 2016 revised IRR of RA No. 9184 allowing the GPPB to amend the IRR, which shall be applied to all procurement activities, the advertisement, posting, or invitation of which were issued after the effectivity of the said amendment.

Additional requirements for the completion of this Contract shall be provided in the **Special Conditions of Contract (SCC).**

2. Advance Payment and Terms of Payment

- 2.1. Advance payment of the contract amount is provided under Annex "D" of the revised 2016 IRR of RA No. 9184.
- 2.2. The Procuring Entity is allowed to determine the terms of payment on the partial or staggered delivery of the Goods procured, provided such partial payment shall correspond to the value of the goods delivered and accepted in accordance with prevailing accounting and auditing rules and regulations. The terms of payment are indicated in the **SCC**.

[Include the following clauses if Framework Agreement will be used:]

2.3. For a single-year Framework Agreement, prices charged by the Supplier for Goods delivered and/or services performed under a Call-Off shall not vary from the prices quoted by the Supplier in its bid.

2.4. For multi-year Framework Agreement, prices charged by the Supplier for Goods delivered and/or services performed under a Call-Off shall not vary from the prices quoted by the Supplier during conduct of Mini-Competition.

3. Performance Security

Within ten (10) calendar days from receipt of the Notice of Award by the Bidder from the Procuring Entity but in no case later than prior to the signing of the Contract by both parties, the successful Bidder shall furnish the performance security in any of the forms prescribed in Section 39 of the 2016 revised IRR of RA No. 9184.*[[Include if Framework Agreement will be used:] In the case of Framework Agreement, the Bidder may opt to furnish the performance security or a Performance Securing Declaration as defined under the Guidelines on the Use of Framework Agreement.<i>]*

4. Inspection and Tests

The Procuring Entity or its representative shall have the right to inspect and/or to test the Goods to confirm their conformity to the Project *{[Include if Framework Agreement will be used:]* or Framework Agreement*]* specifications at no extra cost to the Procuring Entity in accordance with the Generic Procurement Manual. In addition to tests in the **SCC, Section IV (Technical Specifications)** shall specify what inspections and/or tests the Procuring Entity requires, and where they are to be conducted. The Procuring Entity shall notify the Supplier in writing, in a timely manner, of the identity of any representatives retained for these purposes.

All reasonable facilities and assistance for the inspection and testing of Goods, including access to drawings and production data, shall be provided by the Supplier to the authorized inspectors at no charge to the Procuring Entity.

5. Warranty

- 6.1. In order to assure that manufacturing defects shall be corrected by the Supplier, a warranty shall be required from the Supplier as provided under Section 62.1 of the 2016 revised IRR of RA No. 9184.
- 6.2. The Procuring Entity shall promptly notify the Supplier in writing of any claims arising under this warranty. Upon receipt of such notice, the Supplier shall,

repair or replace the defective Goods or parts thereof without cost to the Procuring Entity, pursuant to the Generic Procurement Manual.

6. Liability of the Supplier

The Supplier's liability under this Contract shall be as provided by the laws of the Republic of the Philippines.

If the Supplier is a joint venture, all partners to the joint venture shall be jointly and severally liable to the Procuring Entity.

Section V. Special Conditions of Contract

Notes on the Special Conditions of Contract

Similar to the BDS, the clauses in this Section are intended to assist the Procuring Entity in providing contract-specific information in relation to corresponding clauses in the GCC found in Section IV.

The Special Conditions of Contract (SCC) complement the GCC, specifying contractual requirements linked to the special circumstances of the Procuring Entity, the Procuring Entity's country, the sector, and the Goods purchased. In preparing this Section, the following aspects should be checked:

- a. Information that complements provisions of the GCC must be incorporated.
- b. Amendments and/or supplements to provisions of the GCC as necessitated by the circumstances of the specific purchase, must also be incorporated.

However, no special condition which defeats or negates the general intent and purpose of the provisions of the GCC should be incorporated herein.

Special Conditions of Contract

GCC	
Clause	
1	[List here any additional requirements for the completion of this Contract. The following requirements and the corresponding provisions may be deleted, amended, or retained depending on its applicability to this Contract:]
	Delivery and Documents –
	For purposes of the Contract, "EXW," "FOB," "FCA," "CIF," "CIP," "DDP" and other trade terms used to describe the obligations of the parties shall have the meanings assigned to them by the current edition of INCOTERMS published by the International Chamber of Commerce, Paris. The Delivery terms of this Contract shall be as follows:
	[For Goods supplied from abroad, state:] "The delivery terms applicable to the Contract are DDP delivered [indicate place of destination]. In accordance with INCOTERMS."
	[For Goods supplied from within the Philippines, state:] "The delivery terms applicable to this Contract are delivered [indicate place of destination]. Risk and title will pass from the Supplier to the Procuring Entity upon receipt and final acceptance of the Goods at their final destination."
	Delivery of the Goods shall be made by the Supplier in accordance with the terms specified in Section VI (Schedule of Requirements).
	For purposes of this Clause the Procuring Entity's Representative at the Project Site is <i>[indicate name(s)]</i> .
	Incidental Services –
	The Supplier is required to provide all of the following services, including additional services, if any, specified in Section VI. Schedule of Requirements: <i>Select appropriate requirements and delete the rest.</i>
	a. performance or supervision of on-site assembly and/or start-up of the supplied Goods;
	 b. furnishing of tools required for assembly and/or maintenance of the supplied Goods;
	c. furnishing of a detailed operations and maintenance manual for each appropriate unit of the supplied Goods;
	d. performance or supervision or maintenance and/or repair of the supplied Goods, for a period of time agreed by the parties, provided

that this service shall not relieve the Supplier of any warranty obligations under this Contract; and
 e. training of the Procuring Entity's personnel, at the Supplier's plant and/or on-site, in assembly, start-up, operation, maintenance, and/or repair of the supplied Goods. f. [Specify additional incidental service requirements, as needed.]
The Contract price for the Goods shall include the prices charged by the Supplier for incidental services and shall not exceed the prevailing rates charged to other parties by the Supplier for similar services.
Spare Parts –
The Supplier is required to provide all of the following materials, notifications, and information pertaining to spare parts manufactured or distributed by the Supplier:
Select appropriate requirements and delete the rest.
a. such spare parts as the Procuring Entity may elect to purchase from the Supplier, provided that this election shall not relieve the Supplier of any warranty obligations under this Contract; and
b. in the event of termination of production of the spare parts:
i. advance notification to the Procuring Entity of the pending termination, in sufficient time to permit the Procuring Entity to procure needed requirements; and
ii. following such termination, furnishing at no cost to the Procuring Entity, the blueprints, drawings, and specifications of the spare parts, if requested.
The spare parts and other components required are listed in Section VI (Schedule of Requirements) and the cost thereof are included in the contract price.
The Supplier shall carry sufficient inventories to assure ex-stock supply of consumable spare parts or components for the Goods for a period of [<i>indicate here the time period specified</i> . <i>If not used indicate a time period of three times the warranty period</i>].
Spare parts or components shall be supplied as promptly as possible, but in any case, within [<i>insert appropriate time period</i>] months of placing the order.

Packaging –
The Supplier shall provide such packaging of the Goods as is required to prever their damage or deterioration during transit to their final destination, a indicated in this Contract. The packaging shall be sufficient to withstan- without limitation, rough handling during transit and exposure to extrem temperatures, salt and precipitation during transit, and open storage. Packagin case size and weights shall take into consideration, where appropriate, the remoteness of the Goods' final destination and the absence of heavy handling facilities at all points in transit.
The packaging, marking, and documentation within and outside the package shall comply strictly with such special requirements as shall be express provided for in the Contract, including additional requirements, if any, specific below, and in any subsequent instructions ordered by the Procuring Entity.
The outer packaging must be clearly marked on at least four (4) sides as follow
Name of the Procuring Entity Name of the Supplier Contract Description Final Destination Gross weight Any special lifting instructions Any special handling instructions Any relevant HAZCHEM classifications
A packaging list identifying the contents and quantities of the package is to be placed on an accessible point of the outer packaging if practical. If not practic the packaging list is to be placed inside the outer packaging but outside the secondary packaging.
Transportation –
Where the Supplier is required under Contract to deliver the Goods CIF, CII or DDP, transport of the Goods to the port of destination or such other name place of destination in the Philippines, as shall be specified in this Contract shall be arranged and paid for by the Supplier, and the cost thereof shall be included in the Contract Price.

	Where the Supplier is required under this Contract to transport the Goods to a specified place of destination within the Philippines, defined as the Project Site, transport to such place of destination in the Philippines, including insurance and storage, as shall be specified in this Contract, shall be arranged by the Supplier, and related costs shall be included in the contract price.
	Where the Supplier is required under Contract to deliver the Goods CIF, CIP or DDP, goods are to be transported on carriers of Philippine registry. In the event that no carrier of Philippine registry is available, goods may be shipped by a carrier which is not of Philippine registry provided that the Supplier obtains and presents to the Procuring Entity certification to this effect from the nearest Philippine registry are available but their schedule delays the Supplier in its performance of this Contract the period from when the Goods were first ready for shipment and the actual date of shipment the period of delay will be considered force majeure.
	The Procuring Entity accepts no liability for the damage of Goods during transit other than those prescribed by INCOTERMS for DDP deliveries. In the case of Goods supplied from within the Philippines or supplied by domestic Suppliers risk and title will not be deemed to have passed to the Procuring Entity until their receipt and final acceptance at the final destination.
	Intellectual Property Rights –
	The Supplier shall indemnify the Procuring Entity against all third-party claims of infringement of patent, trademark, or industrial design rights arising from use of the Goods or any part thereof.
2.2	Partial payment is allowed . "The terms of payment shall be as follows: "Supplier shall issue a Statement of Account and corresponding Charge Invoice to the quantity delivered based on the quantity requested. which will be use as basis for payment, until the total amount stipulated per contract are fully delivered, Inspected & Accepted by CMU"
4	The inspections and tests that will be conducted are: [Indicate the applicable inspections and tests]

Section VI. Schedule of Requirements

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of delivery to the project site.

Item Number	Description	Quantity	Total	Delivered, Weeks/Months
	Lot 1			
R.Aguilar				
1	150mmMECHANICALFLOWMETERmetersize:150mmnominaldiametermaximumratedcapacityQmax:Qmax≥600m3/hournominalcapacity for continued dutyQn:Qn≥450m3/hourtransitionalflowQt:Qt≤4m3/hourtransitionalflowQt:Qt≤4m3/hourminimumflowrateQt:Qt≤4m3/hourmetrologicalclassificationmust be on a par orbetterthat hat which is given on the table belowQmax600m3/hallowableerror±2%Qn450m3/hallowableerror±2%Qt4m3/hallowableerror±2%Qmin1.8m3/hallowableerror±2%Qmin1.8m3/hallowableerror±5%maximumreading:10,000,000m3smallestreading:0.005m3maximumadmisibletemperature:mat ≥50°Cregistercan be rotated through 360° to view inanypositioninstallationrequirements:3xDN frontand NOabruptrestrictiondirectlybehindthemeterWith1/4" connection port for pressure sensorssensors	2		
	Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading Pulser Specifications: Simple installation, pulser can be fiited without breaking the meter seal, two differen pulse values, protection rating: IP68, temperature range: Up 50°C Online Data Logger Programming and downloading: via Bluetooth Data viewing: via web portal (unlimeted user accuracy) ± 0.1% of full range, quick release male connection, pressure range of 0-20 bar or higher Digital/flow: bi-directional/option to combine into			

	single log value,		
	max pulse frequency: 1000Hz, switches to event		
	pulse interval timing at low pulse rates		
	Recording travel:		
	at least capable of recording in 1 second up to 24 hours interval		
	24 hours interval memory: at least 4gb of memory material body:		
	estruded 6063 aluminum protection		
	classification: IP 68-fully submersible in depth of		
	1m,		
	power supply: battery operated, minimum		
	operation of 5 years under normal operating		
	conditions web server:		
	capable to display data in chart form, table form,		
	daily summary and alarms cloud based-analytics solution for water network		
	pressure		
	and flow via browser tablet or smartphone		
	capable of detecting logger position in google		
	maps		
	the logger must be capable but not limited to the		
	ff:		
	signal strenght test, export data to excel from web portal.		
	web portal, easy to use free android application allows		
	simple wireless		
	configuration and set-up of the logger via		
	smartphone of		
	tablet, request of instantaneous data viewing via		
	app,		
	with API system that can send your data to webserver or		
	preferred third party data hosting platform		
	minimum required number of channels: 2		
	channels		
	(1x internal pressure, 1 digital flow)		
	(1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter	4	
	(1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter	4	
	(1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Qmax: Qmax ≥	4	
	(1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Qmax: Qmax ≥ 300m3/hour	4	
	(1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Qmax: Qmax ≥	4	
	(1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Qmax: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥	4	
	(1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Qmax: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour minimum flow rate Qt.' Qmin ≤ 0.8m3/hour	4	
	(1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Qmax: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour minimum flow rate Qt:' Qmin ≤ 0.8m3/hour metrological classification must be on a par or	4	
	(1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Qmax: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour minimum flow rate Qt.' Qmin ≤ 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below	4	
	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	4	
	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	4	
	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	4	
	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	4	
	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	4	
	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	4	
	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	4	
	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	4	
	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	4	
2	(1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Qmax: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour minimum flow rate Qt.' Qmin ≤ 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qn 230m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qmin 0.8m3/h allowable error \pm 2% Qmin 0.8m3/h allowable error \pm 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admisible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter	4	
2	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	4	
2	(1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Qmax: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour minimum flow rate Qt.' Qmin ≤ 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qn 230m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qmin 0.8m3/h allowable error \pm 2% Qmin 0.8m3/h allowable error \pm 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admisible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter	4	
2	(1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Qmax: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour minimum flow rate Qt.' Qmin ≤ 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qn 230m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qmin 0.8m3/h allowable error \pm 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admisible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors	4	
2	(1x internal pressure, 1 digital flow)100mmMechanicalFlowmetermetersize:100mmnominaldiametermaximumratedcapacityQmax:Qmax \geq 300m3/hournominalcapacity for continued dutyQn \geq $230m3/hour$ TransitionalflowQt:Qt \geq $230m3/hour$ transitionalflowQt:Qt \leq 1.8m3/hourminimumflowQt:Qt \leq $1.8m3/hour$ metrologicalclassificationmust be on a par orbetter than that which is given on the table belowQmax300 m3/hallowableerror \pm 2% Qn230m3/hallowableerror \pm 2% Qt1.8 m3/hallowableerror \pm 2% Qt1.8 m3/hallowableerror \pm 2% Qmin0.8m3/hallowableerror \pm 2% Qt1.8 m3/hallowableerror \pm 2% Qmin $0.0005m3$ maximumadditionmaximumreading:1,000,000m3smallestreading: $0.0005m3$ maximumreading:3,0005m3	4	
2	(1x internal pressure, 1 digital flow)100mm Mechanical Flowmetermeter size: 100mm nominal diametermaximum rated capacity Qmax: Qmax \geq 300m3/hournominal capacity for continued duty Qn: Qn \geq 230m3/hourtransitional flow Qt: Qt \leq 1.8m3/hourminimum flow rate Qt.' Qmin \leq 0.8m3/hourmetrological classification must be on a par orbetter than that which is given on the table belowQmax 300 m3/h allowable error \pm 2%Qt 1.8 m3/h allowable error \pm 2%Qt 1.8 m3/h allowable error \pm 2%Qmin 0.8m3/h allowable error \pm 5%maximum reading: 1,000,000 m3smallestreading: 0.0005m3maximum admisible temperature: mat \geq 50°Cregister can be rotated through 360° to view inanypositioninstallation requirements: 3xDN front and NOabrupt restriction directly behind the meterWith 1/4" connection port for pressure sensorsMeterAccessories:1. Pulser/Reed switch sensor with 3-meterlengthwireopenended2. stainless steel bolts 8 pieces for flange end	4	
2	(1x internal pressure, 1 digital flow)100mmMechanicalFlowmetermetersize:100mmnominaldiametermaximumratedcapacityQmax:Qmax \geq 300m3/hournominalcapacity for continued dutyQn \geq $230m3/hour$ TransitionalflowQt:Qt \geq $1.8m3/hour$ minimumflowQt:Qt \leq $1.8m3/hour$ minimumflowQt:Qt \leq $1.8m3/hour$ metrologicalclassificationmust be on a par orbetter than that which is given on the table belowQmax300 m3/hallowableerror \pm 2% Qn230m3/hallowableerror \pm 2% Qt1.8 m3/hallowableerror \pm 2% Qt1.8 m3/hallowableerror \pm 2% Qmin0.8m3/hallowableerror \pm 2% Qt1.8 m3/hallowableerror \pm 2% Qmin0.0005m3maximumaddingmaximumreading:1,000,000m3smallestreading:0.0005m3maximumreading:3,000,000m3 </td <td>4</td> <td></td>	4	
2	(1x internal pressure, 1 digital flow)100mmMechanicalFlowmetermetersize:100mmnominaldiametermaximumratedcapacityQmax:Qmax \geq 300m3/hournominalcapacity for continued dutyQn \geq $230m3/hour$ TransitionalflowQt:Qt \geq $1.8m3/hour$ minimumflowQt:Qt \leq 1.8m3/hourminimumflowQt:Qt \leq $1.8m3/hour$ metrologicalclassificationmust be on a par orbetter than that which is given on the table belowQmax300 m3/hallowableerror \pm 2% Qn230m3/hallowableerror \pm 2% Qn230m3/hallowableerror \pm 2% Qt1.8m3/hallowableerror \pm 2% Qmin0.8m3/hallowableerror \pm 2% Qmin0.8m3/hallowableerror \pm 2% Qmin0.8m3/hallowableerror \pm 2% Qt1.8m3/hallowableerror \pm 2% Qmin 360° to view inany </td <td>4</td> <td></td>	4	
2	(1x internal pressure, 1 digital flow)100mmMechanicalFlowmetermetersize:100mmnominaldiametermaximumratedcapacityQmax:Qmax \geq 300m3/hournominalcapacityforcontinueddutyQn \geq \geq 300m3/hourransitionalflowQt:Qt \leq 1.8m3/hourminimumflowQt:Qt \leq 1.8m3/hourminimumflowqt:Qt \leq 1.8m3/hourmetrologicalclassificationmust be on a par orbetter than that which is given on the table belowQmax300m3/hallowableerror \pm 2%Qn230m3/hallowableerror \pm 2%Qt1.8m3/hallowableerror \pm 2%Qt1.8m3/hallowableerror \pm 2%Qmin0.8m3/hallowableerror \pm 2%Qt1.8m3/hallowableerror \pm 2%Qmin0.0005m3maximumreading:1,000,000m3smallestreading:0.0005m3maximumadmisible temperature:mat \geq 50°Cregistercan be rotated through 360° to view inanypositioninstallationrequirements:3xDN front and NOabrupt restrictiondirectly behind the meterWith 1/4"connection port for pressure sensorsMeterAccessories:1. <td< td=""><td>4</td><td></td></td<>	4	
2	100mmMechanicalFlowmeter meter metermetersize:100mmnominal diameter maximum nated capacity Qmax:Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow preventional flow Qt: Qt \leq 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt Qt 1.8 m3/h allowable error \pm 2% Qt Qt 1.8 m3/h allowable error \pm 2% Qmin 0.8m3/h allowable error \pm 2% Qmin 0.8m3/h allowable error \pm 2% Qt n 230m3/h allowable error \pm 2% Qt n 230m3/h allowable error \pm 2% Qt n 230m3/h allowable error \pm 2% Qt n 230m3/h allowable error \pm 2% Qt n n smailest reading: n 0.0005m3 maximum ang position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensorsMeterAccessories: n Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity	4	
2	(1x internal pressure, 1 digital flow)100mm Mechanical Flowmetermetersize:100mm nominaldiametermaximumratedcapacityQmax:Qmax \geq 300m3/hournominalcapacity for continued dutyQn \geq \geq $230m3/hourItransitionalflowQt:Qt \geq1.8m3/hourminimumflowQt:Qt \leq1.8m3/hourminimumflowQt:Qt \leq1.8m3/hourmetrological classificationmust be on a par orbetter than that which is given on the table belowQmax300 m3/h allowableerror \pm2\%Qn230m3/h allowableerror \pm2\%Qn230m3/h allowableerror \pm2\%Qt1.8 m3/h allowableerror \pm2\%Qmin0.8m3/h allowableerror \pm2\%Qt1.8 m3/h allowableerror \pm2\%Qmin0.8m3/h allowableerror \pm2\%Qt1.8 m3/h allowableerror \pm2\%Qmin0.8m3/h allowableerror \pm2\%Qt1.8 m3/h allowableerror \pm2\%0.0005m3maximumreading:1,000,000m3smallestreading:0.0005m3maximumadmisibletemperature:mat \geqnavipositioninstallationrequirements:3xDN front and NOabrupt restrictiondirectly behindthe meterWith 1/4"connection port for pressure se$	4	

1	Simple installation, pulser can be fitted without		
	breaking the meter seal, two different pulse		
	-		
	values,		
	protection rating: IP68, temperature range: Up		
	50°C		
	Online Data Logger		
	Programming and downloading: via Bluetooth		
	Data viewing: via web portal (unlimited user		
	access) antenna: external		
	Analogue/pressure: internal pressure		
	transducer, accuracy		
	\pm 0.1% of full range, quick release male		
	connection,		
	pressure range of 0-20 bar or higher		
	Digital/flow: bi-directional/option to combine into		
	single log value,		
	max pulse frequency: 1000Hz, switches to event		
	pulse interval timing at low pulse rates		
	Recording travel:		
	at least capable of recording in 1 second up to		
	24 hours interval		
	memory: at least 4gb of memory material body:		
	extruded 6063 aluminum protection		
	classification: IP 68-fully submersible in depth of		
	1m, power supply: battery operated, minimum		
	operation of 5 years under normal operating		
	capable to display data in chart form, table form,		
	daily summary and alarms		
	cloud based-analytics solution for water network		
	pressure and flow via browser tablet or		
	smartphone capable of detecting logger position		
	in google maps		
	the logger must be capable but not limited to the		
	ff:		
	signal strength test, export data to excel from		
	web portal,		
	easy to use free android application allows		
	simple wireless		
	configuration and set-up of the logger via		
	smartphone of		
	tablet, request of instantaneous data viewing via		
	app,		
	with API system that can send your data to		
	webserver or		
	preferred third party data hosting platform		
	minimum required number of channels: 2		
	channels		
	(1x internal pressure, 1 digital flow)		
	(17 internai pressure, i uigitai ilow)		
	NOTE: with supply and installation and		
	commissioning		
1	Additional requirements (to be submitted		
	during opening of bids)		
1	Delivery period: 30days, must submit an original		
	copy of catalog/brochure of the data logger,		
	must submit an		
	original or a computer-generated copy of the		
1	data logger		
	manual, must include necessary fittings for each		
	, ,		
	logger		
	logger (Compliance upon delivery), SIM Card inclusive		
	logger (Compliance upon delivery), SIM Card inclusive of year load for data transmission (compliance		
	logger (Compliance upon delivery), SIM Card inclusive of year load for data transmission (compliance upon delivery) supplier must have		
	logger (Compliance upon delivery), SIM Card inclusive of year load for data transmission (compliance upon delivery) supplier must have Manufacturer's Authorization		
	logger (Compliance upon delivery), SIM Card inclusive of year load for data transmission (compliance upon delivery) supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier		
	logger (Compliance upon delivery), SIM Card inclusive of year load for data transmission (compliance upon delivery) supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have		
	logger (Compliance upon delivery), SIM Card inclusive of year load for data transmission (compliance upon delivery) supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier		

(Compliance upon delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from the date of acceptance		

Section VII. Technical Specifications

Notes for Preparing the Technical Specifications

A set of precise and clear specifications is a prerequisite for Bidders to respond realistically and competitively to the requirements of the Procuring Entity without qualifying their Bids. In the context of Competitive Bidding, the specifications (*e.g.* production/delivery schedule, manpower requirements, and after-sales service/parts, descriptions of the lots or items) must be prepared to permit the widest possible competition and, at the same time, present a clear statement of the required standards of workmanship, materials, and performance of the goods and services to be procured. Only if this is done will the objectives of transparency, equity, efficiency, fairness , and economy in procurement be realized, responsiveness of bids be ensured, and the subsequent task of bid evaluation and post-qualification facilitated. The specifications should require that all items, materials and accessories to be included or incorporate all recent improvements in design and materials unless otherwise provided in the Contract.

Samples of specifications from previous similar procurements are useful in this respect. The use of metric units is encouraged. Depending on the complexity of the goods and the repetitiveness of the type of procurement, it may be advantageous to standardize the General Technical Specifications and incorporate them in a separate subsection. The General Technical Specifications should cover all classes of workmanship, materials, and equipment commonly involved in manufacturing similar goods. Deletions or addenda should then adapt the General Technical Specifications to the particular procurement.

Care must be taken in drafting specifications to ensure that they are not restrictive. In the specification of standards for equipment, materials, and workmanship, recognized Philippine and international standards should be used as much as possible. Where other particular standards are used, whether national standards or other standards, the specifications should state that equipment, materials, and workmanship that meet other authoritative standards, and which ensure at least a substantially equal quality than the standards mentioned, will also be acceptable. The following clause may be inserted in the Special Conditions of Contract or the Technical Specifications.

Sample Clause: Equivalency of Standards and Codes

Wherever reference is made in the Technical Specifications to specific standards and codes to be met by the goods and materials to be furnished or tested, the provisions of the latest edition or revision of the relevant standards and codes shall apply, unless otherwise expressly stated in the Contract. Where such standards and codes are national or relate to a particular country or region, other authoritative standards that ensure substantial equivalence to the standards and codes specified will be acceptable.

Reference to brand name and catalogue number should be avoided as far as possible; where unavoidable they should always be followed by the words "*or at least equivalent*." References to brand names cannot be used when the funding source is the GOP.

Where appropriate, drawings, including site plans as required, may be furnished by the Procuring Entity with the Bidding Documents. Similarly, the Supplier may be requested to provide drawings or samples either with its Bid or for prior review by the Procuring Entity during contract execution.

Bidders are also required, as part of the technical specifications, to complete their statement of compliance demonstrating how the items comply with the specification.

Technical Specifications

Item	Specification	Statement of Compliance
		[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross- referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]
	GOODS:	
R.Agu ilar		
1	150mm MECHANICAL FLOW METER meter size: 150mm nominal diameter maximum rated capacity Qmax: Qmax ≥ 600m3/hour nominal capacity for continued duty Qn: Qn ≥ 450m3/hour transitional flow Qt: Qt ≤ 4m3/hour minimum flow rate Qt:' Qmin ≤ 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 600 m3/h allowable error \pm 2% Qn 450m3/h allowable error \pm 2% Qt 4 m3/h allowable error \pm 2% Qmin 1.8m3/h allowable error \pm 2% maximum reading: 10,000,000 m3 smallest reading: 0.005m3 maximum admisible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors	
	Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open ended 2. stainless steel bolts 8 pieces for flange end PN16 and the sensor flange 3. meter flange Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote	

Pulser Specifications: Simple restabilistion, pulser can be fitted without breaking the meter shall lation, pulser can be fitted without breaking, protection rating, IPEA, thereafture may be 30°C Online Data Logger Programming and downbading; via butcoth Data Logger Analogue/pressure: internal pressure transducer, accuracy accuracy accuracy attrans accuracy accuracy accuracy piped provide frequency. UDOH2, a witches to event pulse interval filtering al top-uplea rates Recording tavel, attransducer, accuracy, at least 4gb of manary material body: estimation of the order of the power supply: tatleny operated, minimum operation of 5 yees: under normal operating conditions web server: capable to displication advice bias frequency. UDOH2, a witches disease web server: capable to displication advices anytox table of the mathematic table of the mathematic table of the mathematic table of the acting logger costol in poople maps the signal strangth table, accurate table of the simple prior mathematic table of the acting hogger costol in poople maps the signal strangth table, acquided table webring via sampthematic table of the simple patient in table of the simple table of the simple for table, request of instantaneous datal webring via sampthematic table of the simple patient table accurate table of the simple patient table accurate table of the simple table of the simple size information and your data to besore accuracy accuracy acting table of the fifth signal strangth table accurate table of the simple size information and your data to besore accuracy accurac			
Simple installation, pulser can be titled without breaking the meter scale, two different pulse values, protection after; IPOS, tempesture range: Up 50°C Online D tat Logger Programming and downloading: via Bluetooth Data vewing: via web total (unitmed user access) antenna: external external external accuracy # 0.1% of Uit range, quick release mile connection, pressure range of 0.20 bar or higher Digitation. United total to be event pulse intravio firming at loop pulse rates faccuring sevel. external external accuracy max puble frequency 1000Hz, switches lo event pulse intravio firming at loop pulse rates faccuring is event pulse intravio firming at loop pulse rates faccuring is event pulse intravio firming at loop pulse rates faccuring is event pulse intravio firming at loop pulse rates faccuring is event pulse intravio firming at loop pulse rates faccuring is event pulse intravio firming at loop pulse rates faccuring is event pulse intravio firming at loop pulse rates form, duity summary and alerms doub Based-main/total objection duity summary and alerms doub based-main/total body: mittake duity automation classification factor pressure and flow via browser tablet or smatphone capable of detecting logger position in google maps the logger must to capable but not limited to the fit signal strength test, export data to acel from web portal, easys to use fite android application allow simple wireless configuration and set-up of the logger via simatphone of table, request of instantaneous data vewing via app, with AP system hat can early our data body CM chao 2 channels (1x internal pressure, logits flow) 100mm Mechanie C dhannels; 20m/th/hour transitional flow OC QC ≤ 18m/thour maintrum flow rates CP Quits Connex 2 30m/th/hour maintrum measing to 100000 mil s maintrum measing to 1000000 mil s maintrum measing to 100000 mil s maintrum me		Pulser Specifications:	
the meter seal, two different pulse values, protection attes; IPAS, thereasture angus, UB sPC Online Data Logger Programming and downbading; via Butechth Data viewing; via web potal (unimeted user access) antenna: example and the sease of the sease of the sease accuracy ± 0.1% of full range, quick release male connection, pressure range of 0.20 bar or nigher Digitalfow. bi-directional/option to combine into single log tags frequency; 100Hz, switches to event pulse interval lima; to user accession in the single log frequency; 100Hz, switches to event pulse interval lima; to user actes Recording tradi- at least capable of recording in teacond up 0.24 hours interval memory; at least 4gb of memory, material body; extrude 6003 alumium protection dessication: P 88- fully submersible in depth of tra, power subprise table; graph of the form, daily summary and alarms doub tosefar/ adarts doub tos			
Protection ratic; IPE8, temperature range: Up 50°C Online Data Logger Programming and downloading: via Bluetooth Data Logger Programming and downloading: via Bluetooth Data external Andigue/pressur: internat: external Andigue/pressur: internation external accuracy ±.0.1% of full range, quok release mate connection, pressure range of 0-20 bar or higher Digiti/Wor bidredictional/going in to scond up to 24 hours internal mex.pole frequency: 100/LT, switches to event pute interval timing at too pute rates Recording travel: at least capable of racoting in second up to 24 hours internal memory: at least 4gb of memory material body: estimated memory and cassification: IP 88-fully submersible in depth of 1m. power supply: tatlary operated, minimum operation of 5 years under normal operating conditions we as serve: capable to display data in charl form, table form, daily summary and alarms doud based-analytics solution for weter network pressure and flow via bowser tablet or smatphone display data in charl form, table going maps the logger must be capable bit dologing and pair was pressured in the capable of racotical application allows simple weides configuration and ex-tup of the logger via smatphone of tablet, request of instantical network pressure in the capable of capable bit do data boxel form we pressure in the capable direction allows simple weides configuration and ex-tup of the logger vias matphone of tablet, request of instances data box			
Online Data Logger Programming and downloading: well Builtooth Data viewing: via web portal (unlined user access) antenna: external Analogue/pressure: internal pressure transducer, accuracy ± 0.5% of full range, quick relases male connection, pressure range of 0.20 bar or nigher Digital/tow. biotenetoning/point or combine into single log internal Big frequency: 100Hz, switches to event pulse interval times of point actes Reaction in the single log internal max pulse frequency: 100Hz, switches to event pulse interval times do point actes Reaction in the single statist capable of reacrding in 1 second up to 24 hours internal internal marrory: at least 4gb of memory material body. extrude 6053 aluminum operation of statistican the site summary and across statistican the site of the site of the site summary and across statistican the site of the site doub based analysis per position in gooder maps chub based analysis get position in gooder maps chub based analysis per position in gooder maps chub chub based and the based from web position and capacity for continued data build base statismes and in the reqarest casto cotaber on the tabbis process configuration and setup of			
Programming and downloading via Bluetoth Data viewing via web portal (unlimited user access) antenna: external Anatogue prossure: internal pressure transducer, accuracy ± 0.15% of full range, guick release male connection, pressure range of 0.20 bar or higher Digital flow: bi-directions/option to combine into single log wale, map puble frequency: 1000Hz, switchs to event puble interval timing at low puble rates Recording Travet: at least capable of forceding in 1 second up to 24 hours interval memory: at least 4gb of memory material body: extuded 6053 aluminum protection dessification: IP 68- fully submersible in depth of fm, power supply-tattery operated, minimum operation of 5 years under normal operating conditions web server: capable to display data in chart form, table form, daily summary and alarms doud based-analytics subtion for water network pressure and flow via trooveer tablet or smartphone capable to display data in chart from, table form, daily summary and alarms doud based-analytics subtion for water network pressure and flow via trooveer tablet or smartphone of tablet, request of instancess data webserver or preferred third party data hoseling pairtorm minimum required number of channels: 2 channels (1/timeral pressure, 1/datal flow) 100rm Mechanical Flowmeter materian rate dasafication must be on a pair to bellet than that which is given on the table below Qmax 300 m3h allowable error ± 2% Qin 18 m3h allowable error ± 2% Qin 08m3h allowable error ± 2% Qin 08m3h allowable error ± 2% Qin 08m3h allowable error ± 2% Qin 1.18 m3h allowable error ± 2% Qin 1.18 m3h allowable error ± 2% Qin 08m3h allowable error ± 2% Qin 1.18 m3h allowable error ± 2% Qin 08m3h allowable error ± 2% Qin 1.18 m3h allowable error ± 2% Qin 1.18 m3h allowable error ± 2			
Data viewnig: via web portal (unlimited user access) enterna: external Analogue/pressure: internal pressure transduor, accuracy. ± 0.1% of MI range, guick relases male connection, prossure range of 0.20 bar on higher Digitaliflow: i-bi-rectional/option to combine into single log value, max poise frequency: 1000Hz, switches to event puble interval ming at two puble refers Recording travel: at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body; excitude 6050 alumnin protection dassiticator: IP 68- fully submersible in depth of 1m, power supply: battery protection distribution for water capable to disply dates sublation for water network pressure and based-analycis sublation for vater network pressure and flow via browser tablet or amarthone capable of depth gata sould application allows simple writeles to depth est avoid dap location allows simple writeles flow was browser tablet or amarthone capable of depth gata (application allows simple writeles cond based-analycis Quark Crance 2 S00m3hour minimum required number of channels; 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter material pressure, 1 digital flow) 100mm Mechanical Flowmeter material pressure, 1 digital flow, 1 2 20m/h 100mm Mechanical Flowmeter material pressure, 1 digital flow) 100mm Mechanical Flowmeter material pressure, 1 digital flow) 100mm Mechanical Flowmeter material preside flow digital flow) 100mm </td <td></td> <td></td> <td></td>			
antenna: external Analogue/pressure: Analogue/pressure: iternal pressure transducer, accuracy ±. 0.1% of full range, quick release mole connection, pressure: ange of 0.20 bar or higher Diplatifier Diplatifier bi-detectionaloption to combine into angle log wulke, max puble frequency: max puble frequency: 100Hz, switches to event puble interval timing at two public rates Recording travel: remony: at least 4gb of memory material body; extruded 663 alumnum protection dassification: P84. tumine: automation of the states the source capable to display data in chart form, table form, daily summary and code and memory at least 4gb of memory material body; summary and code and memory and alerns town as browser table form, daily summary and frequency and alerns town as browser table of a smartphone capable of detecting logger position in google mags the logger and body calls at lowal from web portal, easy to use free analytic as able webserver or preferred thick party data hosting platform minimum required number of channels; 100rm Mctanianeous data lewaly the system that can sendy our data to webserver or preferred thick party data hosting platform minimum diversible to continued duil Go. On 2 230m3hour 100rm Mctanianeous data lewalther maximum required number of channels; 100rm Mctanianeous data lewalther maximum required lewalther to the table bedow Omax 300 mRh allowable error		5 S	
Analogua/prosure: Internal pressure transduor; correcy 1.0% of ful range, quick release male connection, pressure range of 0-20 bar on higher Digitalifors. Indirectional option to combine into single log g max pulse frequency: 1000Hz, switches to event pulse interval ming at two pulser rates Rootful gravel: at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body; extruide 4063 alumnin protection dissification: IP 68- fully submersible in depth of 1m, power supply-battery contains web server: capable to display depreted, minimum competition of 5 years under normal operating conditions web server: capable to display depreted, minimum competition of 5 years under normal operating conditions web server: capable to display depathe but not limited to the ff: signal strength test, export data to excel from web protal, easy to use free android application allows simple wrieless configuration and serve of the logger via smartphone minimum required number of channels; 2 channels (1x internal pressure; 1 digital flow) 100mm Mechanical Fiowmeter matimum required number of channels; 2 channels (1x internal pressure; 1 digital flow) 100mm Mechanical Fiowmeter matimum required number of channels; 2 channels (1x internal pressure; 1 digital flow) 2 More Needing; 1 100000 matimum flow rate Q: C min is 2 60m/hour metrological dissification muse bo on a parc better than that which is gione on the table balow Crass X00 m3h allowable error ± 2% Ch 0 Ans/N allowable error ±			
a Corrisy a Corrisy a Di So full range, quick release male connection, prossure range of 0-20 bar or higher Digetallow: bi-directionaloption to combine into single log ing use interval controls into single log ing use interval timing at low puise rates Recording travel: at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body; extruited 605 alumnum protection classification: IP 8-5 tigt submership add for the top of the t			
± 0.1% of Bit lange, quick verses mele connection, pressure range of 0.20 bar on higher Digitaliforu-to-directionaloption to combine into single log thetherad limit at two pulse reals Recording travel: test capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body; each deed 000 slaminum protection classification: IP 8-bit y submersible in depth of 1m, power supply battery operated, minimum operation of 5 years under normal operating conditions web server. capable to display data in chart form, table form, daily summary and alerms doud based-analytics solution for water network pressure and flow via browser tablet or smartphone capable to display data in chart form, table or the fit signal strength test, group data to web form web portal, easy to use free android application allows simple wireleas with Pi system that can send your data to web server or prefered third party data to head in web portal, easy to use free android application allows simple wireleas configuration and set-up of the logger via smartphone of tablet, request of instandences data website party data to head in party data to head i			
pressure range ⁵ of 0.20 bar or higher log wale, max pulse frequency: 1000Hz, switches to event pulse internel timing al low pulse rates Recording travel: at least tapable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body: exture d063 alummus protection Classification: IP 8-6 fully summarsible in depth of travel: claud best of sequerized at in chart form, table form, daily summary and all ans to based-analytics solution for water network pressure and and flow via browser tablet or smartphone capable of delecting logaer position in google maps the logger must be capable to thin limited to the fit: signal strength test, export data to excel from web portal, exist, to use free android application allows simple wireless configuration and sevup of the logger via smartphone of tablet, request of instantaneous data viewing via app. with API system that can send your data to websereror prefered third party data hosting platform minimum relate capable of collimating platform minimum relate capable (platic) 100mm Mechanical Flowmeter		,	
Digital/Box: b-directional/option to combine into single gas puise frequency: 1000/tz, switches to event puise interval limits of two puise rates Recording travel: at least capable of recording in second up to 24 hours interval memory: at least 4 dp of memory material body: extruded 6063 aluminum protection classification: IP 68- fully submersible in depth of fm power supply: battery operated, minimum operation of 5 yeas under normal operating conditions web server: capable to display data in chart form, table form, daily summary and aiarms cloud based-mahylics solution for water network pressure and flow via browser table for smartphone capable of detecting logger position ing cogle maps the logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wifeless configuration and set-up of the logger via smartphone of tablet, request of instantanceus data viewing via app, with API system that can send your data to webserver or preferred finid party data hoscing pletform minimum required number of channels: 2 channels (1x internal pressure, 1 digtal flow) 100m Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capably Q cm Cm ≥ 230m3/hour minimum flow zete QCt: Q min ≤ 0.8m3/hour minimum flow zete QCt: Q min ≤ 0.8m3/hour minimum flow zete QCt: Q min ≤ 0.8m3/hour minimum flow zete lorger via z % Q n 230m3/h allowable error ± 2% Q n 230m3/hour for presure sensors		•	
log wale, max pulse frequency: 1000Hz, switches to event at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body; extruded 6063 aluminum portection classification: IP 68- fully submersible in depth of 1m, power supply: battery operated, minimum operation of 5 years under normal operating conditions web server: capable to display operated, minimum operation cloud based-matrix solution for water network pressure and flow via browser tablet or smartphone capable of detecting logger position in googe maps the logger must be capable but of limited to the fit: signal strength test, exond data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to weberver or preferred third party data to basing platform minimum requed analter of channels. 2 channels (1th interral pressure, digital flow) thereal pressure () digital flow) 100rm Mechanical Flowmeter meter size: 100mm nominal diameter maximum reder departly data to 80m3/hour nominal capacity for continued duty On: On ≥ 230m3/hour transitional flow Ot: Ot ≤ 1 flom3/hour minimum flow ratio en ap are better than that which is given on the table below Omax 300 m/h allowable error ± 2% On 200m3h allowable error ± 2% On 0.8m3/h allowable error ± 2% On 2.8m3/h allowable error ± 2% On 0.8m3/h a			
max pulse frequency: 1000Lz, switches to event eleast capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body: extruded 063 aluminum protection classification: IP 86- fully submersible in depth of 1 m, power supply: battery operated, minimum operation of 5 years under normal operating confidence web server: capable to display data in chart form, table form, daily summary and flow via browser tablet or smartphone capable of display (logger position ing opger maps the logger must be capable but not limited to the fif signal strength test: export data to excel from web potal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of table, request of instantaneous data viewing via app, with AP system that can send your data webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter metrol size, 100mm nominal allowable error ± 2% On 230m3/hour 100mm Qit Ol Cl ≤ 1 8m3/hour minimum flow rate Ol Cl ≤ 1 8m3/hour minimum flow rate Ol Cl ≤ 1 8m3/hour metrological classification mustbe on apar or better than that which is given on the table below Ornax 300 m3/h allowable error ± 2% On 0.8m3/h allowable eroror ± 2% On 0.8m3/h allowable error ± 2% On			
all east interval timing all low pulse rates Recording travel: ainterval interval memory: at least 4gb of memory material body: extruded 6053 aluminum portection classification: P8- fully submarsible indexide for aluminum operation of 5 years under normal operating conditions web server: capable to display data in chart form, table form, daily summary and alarms cloud based-analytics solution for water network pressure and flow via browser tablet or smartphone capable of deleteding logger position in google maps the logger must be capable but not limited to the ff. signation and set-up of the logger via smartphone of tables, request of instananceus data viewing via app, with API system that can send your data to webserver or prefered hird party data hostion palform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) On: 0n ≥ 230m3/hour transitional (apacity for continued duty On: 0n ≥ 230m3/hour memory all allowable error ± 2% Qin 18 m3/h allowable error ± 2% Qin Qin 0.8 m3/hour memory mainsileat frange assimum reading: 3000 M3/hour minimum flow ratel			
at least capable of recording in 1 second up to 24 hours interval. memory: at least 4gb of memory material body: extruded 6003 attimum protection classification: 1P8- fully submersible in depth of in, power supply: battery operated, minimum operation of 5 years under norma operating conditions web server: capable to display data in chart form, table form, daily summary and aiarms cloud based-analytics solution for water network pressure and flow via browser tablet or smartphone capable of detecting logger position in googt maps the logger must be capable but not limited to the ff. signal strength test, scond data to exclose from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required canserdy our data to webserver or preferred third party. 1 digital flow) 100mm Mechanical measimum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qt 1.8 m3/h allowable error ± 2%			
interval memory: at least 4pb of memory material body: extruded 6063 aluminum protection classification: IP 66- fully submersible in depth of 1m, power supply battery operated, minimum operation of 5 years under normal operating conditions web server: ccapable to disply date in chart form, table form, daily summary and alarms cloub based-analytics solution for water network pressure and flow via browser tablet or smartphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff. signal strength test, export data to excel from web portal, easy to use free android application allows simple writeless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data veiwing via app, with API system that can send your data to webserver or preferred triat party data hosting plefform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour metrological classification must be on apar or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qin 18 m3/h allowable error ± 2% Qin			
among: at least 4gb of memory material body: extuded 6063 aluminum protection classification: IP 68- fully submersible in depth of in, power supply: battery operated, minimum operation of 5 years under normal operating conditions web server: capable to display data in chart form, table form, daily summary and alarms cloud based-analytics solution for water network pressure and flow via browser tablet or smatphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff. signal strength test, export data to exclose more bortal, easy to use free android application allows simple wireless configuration and set-up of the logger via smatphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter maximum rated capacity 0 max: Cmax 2 300m3/hour nominal capacity for continued daty Qn: Cn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour minimum flow rate Qt: Q min ≤ 0.8m3/hour minimum flow rate Qt: Q min ≤ 0.8m3/hour minimum flow rate Qt: Q min ≤ 0.8m3/hour minimum admissible temperature: mat ≥ 50°C Qin 2.80m3/h allowable error ± 2% Qin 2.80m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 5% maximum admissible temperature: mat ≥ 50°C register can be rotlead through 300° to view in any position instalation requirements: 30N fort and NO 3 maintum admissible temperature: mat ≥ 50°C register can be rotlead through 300° to view in any position instalation requirements: 30N fort and NO 3, meter flange gaskets Pulse Output exclicitor to view in any position instalation requirements: 30N fort and NO 3, meter flange gaskets Pulse Out		at least capable of recording in 1 second up to 24 hours	
extrude3 6053 aluminum optection classification: IP 65- fully submessible in depth of 1m, power supply-battery operated, minimum operation of 5 years under normal operating conditions web server: capable to displey tatin chart from, table form, daily summary and alarms cloud based-analytics solution for water network pressure and flow via browser tablet or smatphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff. signal strength test, export data to exclose from web portal, easy to use free ant/oid application allows simple wireless. configuration and set-up of the logger via smatphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity On ax: Omax 2 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour micrological classification must be on a par or better than that which is given on the table below Qraxa: 300 m3/h allowable error ± 2% Qi 18 m3/h allowable error ± 2% Qi 18 m3/h allowable error ± 2% Qi 18 m3/h allowable error ± 5% maximum reading: 1.000.000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated frivog13.50N fort and NO ayout restriction port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainess steel boits 8 pieces for fange end PN16 3. meter fange gaskets Pulse Output Connectivity for data logging or remote reading			
extrude3 6053 aluminum optection classification: IP 65- fully submessible in depth of 1m, power supply-battery operated, minimum operation of 5 years under normal operating conditions web server: capable to displey tatin chart from, table form, daily summary and alarms cloud based-analytics solution for water network pressure and flow via browser tablet or smatphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff. signal strength test, export data to exclose from web portal, easy to use free ant/oid application allows simple wireless. configuration and set-up of the logger via smatphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity On ax: Omax 2 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour micrological classification must be on a par or better than that which is given on the table below Qraxa: 300 m3/h allowable error ± 2% Qi 18 m3/h allowable error ± 2% Qi 18 m3/h allowable error ± 2% Qi 18 m3/h allowable error ± 5% maximum reading: 1.000.000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated frivog13.50N fort and NO ayout restriction port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainess steel boits 8 pieces for fange end PN16 3. meter fange gaskets Pulse Output Connectivity for data logging or remote reading		memory: at least 4gb of memory material body:	
fully submersible in depth of fm, power supply: battery operated, minimum operation of 5 years under normal operating conditions web server: capable to display data in chart form, table form, daily summary and alarms cloud based-analytics solution for water network pressure and flow via browser tablet or smartphone capable of discling logger position in google maps the logger must be capable but not limited to the ff. signal strength test, export data to exosit from web portal, easy to use free and/oid application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, wireless configuration and set-up of the logger via smartphone of (1x internal pressure, 1 digital flow) 100mm Mchanels: 2 channels (1x internal pressure, 1 digital flow) capacity for continued duty Qn: Qn ≥ 230m3/hour nominum required and to appar to better than that which is given on the table below Qmax 300 mAh allowable error ± 2% Qin 230m3/h allowable error ± 2% Qin Qin 18 m3/h allowable error ± 2% Qin Qin 030m3/h al		, , , , ,	
power supply: battery operated, minimum operation of 5 years under normal operating conditions web server: capabile to disply data in chart form, table form, daily summary and and flow via browser tablet or smatphone capabile of detecting logger position in google maps the logger must be capable but not limited to the fit: signal strength test, export data to excel from web potal, easy to use free android application allows simple wireless configuration and set-up of the logger via smatphone of tablet, request of instantaneous data veiwing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required capacity for continued duty Qu: Ch ≥ 100mm Mechanical Forwmeter mater size: 100mm nominal diameter maximum read capacity for continued duty Qu: Ch ≥ 1.8m3/hour minimum flow rate Qut': 1 Sim Sim Allowate metrological classification must be on a par or better than that which is given on the table below Qm 2.800 m3/h allowable error ± 2% Qin 0.80m3/h allowable maximum reading: 1,000,000 m3 <		·	
2 version under normal operating conditions web server: capable to display data in chart form, table form, daily summary and and flow via browser tablet or smartphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or prefered nitide number of channels: 2 channels (1x) internal pressure, 1 digital flow) 100mm Mechanical remer size: 100mm nominal diameter maximum artied capacity Q max. Cmax ≥ 300m3/hour nominal capacity for continued duly Qn: Qn ≥ 230m3/hour transitional flow Qit Qit Q10 0.05m3/h allowable error ± 2% Qn 200m3/h allowable error ± 2% Qn 200m3/h allowable error ± 2% Qit 1.8 m3/h allowable error ± 2% Qit 1.8 m3/h allowable error ± 2% Qit		,	
2 Copable to display data in chart form, table form, daily surmary and alarms cloud based-analytics solution for water network pressure and flow via browser tablet or smartphone capable of detecting logger position in google maps the logger must be capable but not limited to the fit signal strength test, export data to excel from web portal, easy to use free android application allows simple writeless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with AP system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal diameter maximum rated C1 Q min ≤ 0.8m3/hour minimum flow rate Q1 C m is 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 5% maximum reading: 1.000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can he orticated flowup3 80° to view in any position installation requirements: 3xDN front and ND synth restriction directly behind the meter With 1/4° connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire oper-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flang gaskets Pulse Output Connectivity for data logging or remote reading.			
2 summary variant and alarms cloud based-analytics solution for water network pressure and flow via browser tablet or smartphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of table, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred preferred third party data hosting platform minimum required number of channels. 2 channels (1'x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum required number of that network pressure 230m3/hour transitional flow via: Diamoter 230m3/hour transitional flow via: 0.8.m3/hour 230m3/hour maximum admissible temperature: maximum admissible temperature: maximum admissible temperature: maximum admissible temperature: Qin 0.8m3/h allowable error ± 2% Qin <td< td=""><td></td><td></td><td></td></td<>			
cloud based-analytics solution for water network pressure and flow via browser tablet or smartphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff. signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels. 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter meter size: 100mm nominal diameter maximum rate dapedity 0 ms. Cmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour minimum flow rate Qt: Q min ≤ 0.8m3/hour metrodogical classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% QL 1.8 m3/h allowable error ± 5% maximum adminsible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position instalations requirements: 3.DN front and NO abrupt restriction directly behind the meter With 1/4 connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stanless steel bots 8 pieces for flange gaskets Pulse Output connectivity for data logging or remote reading			
2 Pressure and flow via browser tablet or smartphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff. signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred thrid party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Prowmeter maximum rated capacity Qr max: Qnmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour meter size: 100m Qft allowable error ± 2% Qn 230m3/h allowable error ± 2% Qn 320m3/h allowable error ± 2% Qn 0.00m3/h allowable error ± 5% maximum admissible temperature: mat ≥ 50°C register can be rotated th			
and flow via browser tablet or smartphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of table, request of instantaneous data viewing via app, with AP1 system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Formation and set-up of the logger via smartphone of z30m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour minimum flow rate Qt: Q min ≤ 0.8m3/hour minimum more and power ± 2% Qn 230m3/h allowable error ± 2% Q1 1.8 m3/h allowable error ± 5% maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position instalation requirements: 3.30M forint and NO			
2 Accessories:		•	
2 Weter Accessories: 0.0005m3 2 Weter Accessories: 0.0005m3 2 Meter Accessories: 0.0005m3 3 meter fange and/or participant with any source of the set of the			
signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to vebserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter nearer 100mm Mechanical 7 100mm Mechanical 7 100mm Mechanical 7 100mm Nechanical 7 100mm Nethania 8 100mm Nominal cipacity 9 00m 10mm ≤ 0.0m3/hour 1 10mm flow rate 2% 1 10mm flow rate 2% 1 18 3/h< allowable			
2 easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter meter size: 100mm ondinal diameter maximum rated capacity Q max. Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour minimum flow Qt: Qt ≤ 1.8m3/hour metrological casification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qn 203m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 5% maximum admissible temperature: mat ≥ 50°C register can be rotated through 30° to view in any position installation requirements: 3x0N front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity: the meter shall have pulse output connectivity: the meter shall have pulse output connectivity: that meter meter mater shall have pulse output connectivity: that meter flange gaskets Pulse			
2 wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with AP1 system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter meter size: 100mm Mechanical 100mm Mechanical Flowmeter maximum rated capacity Q max. Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qn 230m3/h allowable error ± 2% Qit 1.8 m3/h allowable error ± 2% Qit 0.8m3/h allowable error ± 2% Qit 1.8 m3/h allowable error ± 2% Qit 1.8 m3/h allowable error ± 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Quiput 3. meter flange gaskets Pulse Pulse Output Connectivity: the meter shall have pulse output connectivity or data logging or remote			
2 configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour minimum flow rate Qt: Q min ≤ 0.8m3/hour minimum flow rate Qt: Q min ≤ 0.8m3/hour metrological classification must be on a par or bater than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qt 1.8 m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 5% maximum reading: 1.000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be totated through 360° to view in any position installation requirements: 3x0N front and NO abrupt restriction directly behind the meter With 1/4° connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity: the meter is reading or remote reading		easy to use free android application allows simple	
2 tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qn 230m3/h allowable error ± 2% Qit 1.8 m3/h allowable error ± 2% Qit 0.8m3/h allowable error ± 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4° connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading			
2 tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qn 230m3/h allowable error ± 2% Qit 1.8 m3/h allowable error ± 2% Qit 0.8m3/h allowable error ± 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4° connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading		configuration and set-up of the logger via smartphone of	
2 with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm Mechanical idameter maximum rated capacity O max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour 1.8m3/hour minimum flow rate Qt: Q min ≤ 0.8m3/hour netrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 50°C register can be rotated through 360° to view in any position installation requirements: 3XDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire connectivity: the meter shall have pulse output Connectivity: the meter shall have pulse output connectivity: the meter shall have pulse output connectivity: for metor frange pulse Output Connectivity:	1		
2 preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Cmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qn 230m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 5% maximum reading: 1.000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity; the meter shall have pulse output connectivity for data logging or remote reading	1		
2 minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity (2 max: Cmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qt 1.8 m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 5% maximum reading: 1.000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity for data logging or remote reading		o 111	
(1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity Qn ≥ 230m3/hour transitional flow Qt Qt ≤ 1.8m3/hour transitional flow Qt Qt ≤ 1.8m3/hour minimum flow red L': Q min ≤ 0.8m3/hour meter iside on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qt 1.8 m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors 1.9User/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16		with API system that can send your data to webserver or	
100mm Mechanical Flowmeter imaticum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour minimum flow rate Qt: Q min ≤ 0.8m3/hour minimum flow rate Qt: Q min ≤ 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Q1 230m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 5% maximum reading: 1,000.000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Quise Output Connectivity: the meter shall have pulse output connectivity for data logging or rending		with API system that can send your data to webserver or preferred third party data hosting platform	
2 meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour minimum flow Qt: Qt ≤ 1.8m3/hour minimum flow Qt: Qt ≤ 1.8m3/hour minimum flow rate Qt: Qt ≤ 1.8m3/hour minimum flow At: Qt ≤ 1.8m3/hour meter size no table below Qmax 300 m3/h allowable error ± 2% Qt 1.8 m3/h allowable error ± 2% Qt 1.8 m3/h allowable error ± 2% Qti 1.8 m3/h allowable error ± 2% Qti 1.8 m3/h allowable error ± 2% Qti 1.8 m3/h allowable error ± 5% maximum reading: 0.0005m3		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels	
2 meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour minimum flow Qt: Qt ≤ 1.8m3/hour minimum flow Qt: Qt ≤ 1.8m3/hour minimum flow Ret 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qt 1.8 m3/h allowable error ± 2% Qin 0.8m3/h allowable otomot maximum smaximum reading: 0.00005m3 maximum admatins		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels	
2 maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qn 230m3/h allowable error ± 2% Qi 1.8 m3/h allowable error ± 2% Qt 1.8 m3/h allowable error ± 2% Qi 0.0005m3 maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity for data logging or remote reading Connectivity for data		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow)	
230m3/hour rtransitional flow Qt: Qt ≤ 1.8m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour minimum flow rate Qt:' Q min ≤ 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qn 230m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange Queer Connectivity: the meter shall have pulse output connectivity the meter shallave pulse output c		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter	
230m3/hour 230m3/hour transitional flow Qt: Qt: Stam3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qn 230m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum adiovable error ± 5% maximum reading: 0.0005m3 maximum reading: 0.0005m3 maximum adiovable error ± 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange Pulse Output Connectivity: the meter shall have pulse output connecti		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter	
2 transitional flow Qt: Qt ≤ 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qn 230m3/h allowable error ± 2% Qit 1.8 m3/h allowable error ± 2% Qit 0.8m3/h allowable error ± 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour	
2 minimum flow rate Qt.' Q min ≤ 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qn 230m3/h allowable error ± 2% Qit 1.8 m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse 0. uptut Connectivity; the meter shall have pulse output connectivity for data logging or remote reading		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical flow) Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥	
2 metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qn 230m3/h allowable error ± 2% Qi 1.8 m3/h allowable error ± 2% Qi 1.8 m3/h allowable error ± 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour	
2 that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qt 1.8 m3/h allowable error ± 2% Qt 1.8 m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity the meter shall have pulse output connectivity for data logging or remote reading		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour	
2 that which is given on the table below Qmax 300 m3/h allowable error ± 2% Qt 1.8 m3/h allowable error ± 2% Qt 1.8 m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity the meter shall have pulse output connectivity for data logging or remote reading		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour	
Qmax 300 m3/h allowable error ± 2% Qn 230m3/h allowable error ± 2% Qt 1.8 m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity: the meter shall have pulse output connectivity for data logging or remote reading		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour minimum flow rate Qt:' Q min ≤ 0.8m3/hour	
Qn 230m3/h allowable error ± 2% Qt 1.8 m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 2% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat<		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal capacity for continued duty Qn: Qn ≥ 230m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour minimum flow rate Qt:' Q min ≤ 0.8m3/hour metrological classification must be on a par or better than	
Qt 1.8 m3/h allowable error ± 2% Qin 0.8m3/h allowable error ± 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal clameter ransitional flow Qt: Qt ≤ 1.8m3/hour transitional flow Qt: Qt ≤ 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below that	
Qin 0.8m3/h allowable error ± 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax ≥ 300m3/hour nominal clameter transitional flow Qt: Qt ≤ 1.8m3/hour transitional flow Qt: Qt ≤ 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error ± 2%	
2 maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) $\begin{array}{c c c c c c c c c c c c c c c c c c c $	
2 smallest reading: 0.0005m3 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) $\begin{array}{c c c c c c c c c c c c c c c c c c c $	
2 maximum admissible temperature: mat ≥ 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors 2 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 5%	
2 register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors 8 Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) $\begin{array}{c c c c c c c c c c c c c c c c c c c $	
2 position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour minimum flow rate Qt:' Q min \leq 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 2% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3	
2 abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour minimum flow rate Qt:' Q min \leq 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 2% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat \geq 50°C	
2 With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or reading		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 2% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat \geq 50°C register can be rotated through 360° to view in any	
Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 2% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat \geq 50°C register can be rotated through 360° to view in any	
1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading		with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) $\begin{array}{c c c c c c c c c c c c c c c c c c c $	
1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading	2	with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour minimum flow rate Qt:' Q min \leq 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 2% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat \geq 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter	
open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading	2	with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour minimum flow rate Qt:' Q min \leq 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 2% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat \geq 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter	
open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading	2	with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour minimum flow rate Qt:' Q min \leq 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 2% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat \geq 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors	
2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading	2	with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels $(1x internal pressure, 1 digital flow)$ 100mmMechanicalFlowmeter meter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensorsMeterAccessories:	
3. meter flange gaskets Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading	2	with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels $(1x internal pressure, 1 digital flow)$ 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 5% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat \geq 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensorsMeterAccessories: 1. Pulser/Reed switch sensor with 3-meter length wire	
Pulse Output Connectivity: the meter shall have pulse output connectivity for data logging or remote reading	2	with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels $(1x internal pressure, 1 digital flow)$ 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat \geq 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended	
the meter shall have pulse output connectivity for data logging or remote reading	2	with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour minimum flow rate Qt:' Q min \leq 0.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 2% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat \geq 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16	
logging or remote reading	2	with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qn 230m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qit 0.8m3/h allowable error \pm 2% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat \geq 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange	
	2	with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat \geq 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity:	
	2	with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qin 0.8m3/h allowable error \pm 2% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat \geq 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity; the meter shall have pulse output connectivity for data	
Pulser Specifications:	2	with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow) 100mm Mechanical Flowmeter meter size: 100mm nominal diameter maximum rated capacity Q max: Qmax \geq 300m3/hour nominal capacity for continued duty Qn: Qn \geq 230m3/hour transitional flow Qt: Qt \leq 1.8m3/hour metrological classification must be on a par or better than that which is given on the table below Qmax 300 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% Qt 1.8 m3/h allowable error \pm 2% maximum reading: 1,000,000 m3 smallest reading: 0.0005m3 maximum admissible temperature: mat \geq 50°C register can be rotated through 360° to view in any position installation requirements: 3xDN front and NO abrupt restriction directly behind the meter With 1/4" connection port for pressure sensors Meter Accessories: 1. Pulser/Reed switch sensor with 3-meter length wire open-ended 2. stainless steel bolts 8 pieces for flange end PN16 3. meter flange gaskets Pulse Output Connectivity; the meter shall have pulse output connectivity for data logging or remote reading	

Simple installation, pulser can be fitted without breaking the meter seal, two different pulse values, protection rating: IP68, temperature range: Up 50°C Online Data Logger Programming and downloading: via Bluetooth Data viewing: via web portal (unlimited user access) antenna: external Analogue/pressure: internal pressure transducer, accuracy ± 0.1% of full range, quick release male connection, pressure range of 0-20 bar or higher Digital/flow: bi-directional/option to combine into single log value, max pulse frequency: 1000Hz, switches to event pulse interval timing at low pulse rates Recording travel: at least capable of recording in 1 second up to 24 hours interval memory: at least 4gb of memory material body: extruded 6063 aluminum protection classification: IP 68- fully submersible in depth of 1m, power supply: battery operated, minimum operation of 5 years under normal operating conditions web server: capable to display data in chart form, table form, daily summary and alarms cloud based-analytics solution for water network pressure and flow via browser tablet or smartphone capable of detecting logger position in google maps the logger must be capable but not limited to the ff: signal strength test, export data to excel from web portal, easy to use free android application allows simple wireless configuration and set-up of the logger via smartphone of tablet, request of instantaneous data viewing via app, with API system that can send your data to webserver or preferred third party data hosting platform minimum required number of channels: 2 channels (1x internal pressure, 1 digital flow)	
NOTE: with supply and installation and commissioning Additional requirements (to be submitted during opening of bids) Delivery period: 30days, must submit an original copy of catalog/brochure of the data logger, must submit an original or a computer-generated copy of the data logger manual, must include necessary fittings for each logger (Compliance upon delivery), SIM Card inclusive of 1 year load for data transmission (compliance upon delivery), supplier must have Manufacturer's Authorization Certificate specific for this project, Supplier should have ISO 9001:2015 Certificates, Warranty (Compliance upon	
delivery): all meters shall be guaranteed against defects in workmanship and materials for a period of one (1) year from the date of acceptance	

Checklist of Bidding Documents for Procurement of Goods and Services

Documents should be arranged as per this checklist. Kindly provide folders or guides, dividers and ear tags with appropriate labels.

The Technical Component (First Envelope) shall contain the following:

1. Eligibility Requirements.

Class "A" Documents

Legal Documents

(a) Valid PhilGEPS Registration Certificate (Platinum Membership) (all pages) in accordance with Section 8.5.2 of the IRR;

Technical Documents

- (b) Statement of the prospective bidder of all its ongoing government and private contracts, including contracts awarded but not yet started, if any, whether similar or not similar in nature and complexity to the contract to be bid; within the relevant period in the bidding documents. The Statement shall include all information required in the PBDs prescribed by the GPPB. (*Sample form-Form No. 3*). The duly signed form shall still be submitted even if the bidder has no on-going contract.
- (c) Statement of the prospective bidder identifying its **Single Largest Completed Contract (SLCC)** similar to the contract to be bid, equivalent to at least fifty percent (50%) of the ABC supported with contract/purchase order, end-user's acceptance of officials receipt(s) issued for the contract, within the relevant periods provided in the Bidding Documents. The statement shall include all information required in the PBDs prescribed by the GPPB. (sample form-Form No. 4)
 - (d) The prospective bidder's audited financial statements, showing, among others, the prospective bidder's total and current assets and liabilities, stamped "received" by the BIR or its duly accredited and authorized institutions, for the preceding calendar year which should not be earlier than two (2) years from the date of bid submission.
- (e) Original copy of Bid Security. If in the form of a Surety Bond, submit also a certification issued by the Insurance Commission;

<u>or</u>

Original copy of Notarized Bid Securing Declaration;

- (f) Scheduled VI- Schedule of Requirements with signature of Bidder's authorized representative.
- (g) Original duly signed Omnibus Sworn Statement (OSS);

and if applicable, Original Notarized Secretary's Certificate in case of a corporation, partnership, or cooperative; or Original Special Power of Attorney of all members of the joint venture giving full power and authority to its officer to sign the OSS and do acts to represent the Bidder. (sample Form-Form No. 7)

Financial Documents

(h) The prospective bidder's computation of Net Financial Contracting Capacity (NFCC); (sample form-Form No.5)

<u>or</u>

A committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation.

Class "B" Documents

FINANCIAL COMPONENT (SECOND ENVELOPE)

- (a) Original of duly signed and accomplished Financial Bid Form; (sample form-Form No. 1)
- (b) Original of duly signed and accomplished Price Schedule(s). (sample form-Form No. 2)

FORMS

Republic of the Philippines



Omnibus Sworn Statement (Revised)

[Shall be submitted with the Bid]

REPUBLIC OF THE PHILIPPINES)

CITY/MUNICIPALITY OF _____) S.S.

AFFIDAVIT

I, [Name of Affiant], of legal age, [Civil Status], [Nationality], and residing at [Address of Affiant], after having been duly sworn in accordance with law, do hereby depose and state that:

1. [Select one, delete the other:]

[If a sole proprietorship:] I am the sole proprietor or authorized representative of [Name of Bidder] with office address at [address of Bidder];

[If a partnership, corporation, cooperative, or joint venture:] I am the duly authorized and designated representative of [Name of Bidder] with office address at [address of Bidder];

2. [Select one, delete the other:]

[If a sole proprietorship:] As the owner and sole proprietor, or authorized representative of [Name of Bidder], I have full power and authority to do, execute and perform any and all acts necessary to participate, submit the bid, and to sign and execute the ensuing contract for [Name of the Project] of the [Name of the Procuring Entity], as shown in the attached duly notarized Special Power of Attorney;

[If a partnership, corporation, cooperative, or joint venture:] I am granted full power and authority to do, execute and perform any and all acts necessary to participate, submit the bid, and to sign and execute the ensuing contract for [Name of the Project] of the [Name of the Procuring Entity], as shown in the attached [state title of attached document showing proof of authorization (e.g., duly notarized Secretary's Certificate, Board/Partnership Resolution, or Special Power of Attorney, whichever is applicable;)];

3. [Name of Bidder] is not "blacklisted" or barred from bidding by the Government of the Philippines or any of its agencies, offices, corporations, or Local Government Units, foreign government/foreign or international financing institution whose blacklisting rules have been recognized by the Government Procurement Policy Board, <u>by itself or by</u> <u>relation, membership, association, affiliation, or controlling interest with another</u> <u>blacklisted person or entity as defined and provided for in the Uniform Guidelines</u> <u>on Blacklisting:</u>

- 4. Each of the documents submitted in satisfaction of the bidding requirements is an authentic copy of the original, complete, and all statements and information provided therein are true and correct;
- 5. [Name of Bidder] is authorizing the Head of the Procuring Entity or its duly authorized representative(s) to verify all the documents submitted;

6. [Select one, delete the rest:]

[If a sole proprietorship:] The owner or sole proprietor is not related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

[If a partnership or cooperative:] None of the officers and members of [Name of Bidder] is related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

[If a corporation or joint venture:] None of the officers, directors, and controlling stockholders of [Name of Bidder] is related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

- 7. [Name of Bidder] complies with existing labor laws and standards; and
- 8. *[Name of Bidder]* is aware of and has undertaken the responsibilities as a Bidder in compliance with the Philippine Bidding Documents, which includes:
 - a. Carefully examining all of the Bidding Documents;
 - b. Acknowledging all conditions, local or otherwise, affecting the implementation of the Contract;
 - c. Making an estimate of the facilities available and needed for the contract to be bid, if any; and
 - d. Inquiring or securing Supplemental/Bid Bulletin(s) issued for the [Name of the Project].
- 9. *[Name of Bidder]* did not give or pay directly or indirectly, any commission, amount, fee, or any form of consideration, pecuniary or otherwise, to any person or official, personnel or representative of the government in relation to any procurement project or activity.

10. In case advance payment was made or given, failure to perform or deliver any of the obligations and undertakings in the contract shall be sufficient grounds to constitute criminal liability for Swindling (Estafa) or the commission of fraud with unfaithfulness or abuse of confidence through misappropriating or converting any payment received by a person or entity under an obligation involving the duty to deliver certain goods or services, to the prejudice of the public and the government of the Philippines pursuant to Article 315 of Act No. 3815 s. 1930, as amended, or the Revised Penal Code.

IN WITNESS WHEREOF, I have hereunto set my hand this ____ day of ____, 20___ at ____, Philippines.

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE]

[Insert signatory's legal capacity]

Affiant

[Jurat]

[Format shall be based on the latest Rules on Notarial Practice]

Bid Securing Declaration Form

[Shall be submitted with the Bid if bidder opts to provide this form of bid security]

REPUBLIC OF THE PHILIPPINES)

CITY OF ______) S.S.

BID SECURING DECLARATION

Project Identification No.: [Insert number]

To: [Insert name and address of the Procuring Entity]

I/We, the undersigned, declare that:

- 1. I/We understand that, according to your conditions, bids must be supported by a Bid Security, which may be in the form of a Bid Securing Declaration.
- 2. I/We accept that: (a) I/we will be automatically disqualified from bidding for any procurement contract with any procuring entity for a period of two (2) years upon receipt of your Blacklisting Order; and, (b) I/we will pay the applicable fine provided under Section 6 of the Guidelines on the Use of Bid Securing Declaration, within fifteen (15) days from receipt of the written demand by the procuring entity for the commission of acts resulting to the enforcement of the bid securing declaration under Sections 23.1(b), 34.2, 40.1 and 69.1, except 69.1(f),of the IRR of RA No. 9184; without prejudice to other legal action the government may undertake.
- 3. I/We understand that this Bid Securing Declaration shall cease to be valid on the following circumstances:
 - a. Upon expiration of the bid validity period, or any extension thereof pursuant to your request;
 - b. I am/we are declared ineligible or post-disqualified upon receipt of your notice to such effect, and (i) I/we failed to timely file a request for reconsideration or (ii) I/we filed a waiver to avail of said right; and
 - c. I am/we are declared the bidder with the Lowest Calculated Responsive Bid, and I/we have furnished the performance security and signed the Contract.

IN WITNESS WHEREOF, I/We have hereunto set my/our hand/s this _____ day of [month] [year] at [place of execution].

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE]

[Insert signatory's legal capacity]

Affiant

[Jurat]

[Format shall be based on the latest Rules on Notarial Practice]

Bid Form for the Procurement of Goods

[Shall be submitted with the Bid]

BID FORM

Date: _____

Project Identification No. : _____

To: [name and address of Procuring Entity]

Having examined the Philippine Bidding Documents (PBDs) including the Supplemental or Bid Bulletin Numbers *[insert numbers]*, the receipt of which is hereby duly acknowledged, we, the undersigned, offer to *[supply/deliver/perform]* [description of the Goods] in conformity with the said PBDs for the sum of [total Bid amount in words and figures] or the total calculated bid price, as evaluated and corrected for computational errors, and other bid modifications in accordance with the Price Schedules attached herewith and made part of this Bid. The total bid price includes the cost of all taxes, such as, but not limited to: [specify the applicable taxes, e.g. (i) value added tax (VAT), (ii) income tax, (iii) local taxes, and (iv) other fiscal levies and duties], which are itemized herein or in the Price Schedules,

If our Bid is accepted, we undertake:

- a. to deliver the goods in accordance with the delivery schedule specified in the Schedule of Requirements of the Philippine Bidding Documents (PBDs);
- b. to provide a performance security in the form, amounts, and within the times prescribed in the PBDs;
- c. to abide by the Bid Validity Period specified in the PBDs and it shall remain binding upon us at any time before the expiration of that period.

[Insert this paragraph if Foreign-Assisted Project with the Development Partner:

Commissions or gratuities, if any, paid or to be paid by us to agents relating to this Bid, and to contract execution if we are awarded the contract, are listed below:

Name and address Amount and Purpose of agent Currency Commission or gratuity

(if none, state "None")]

Until a formal Contract is prepared and executed, this Bid, together with your written acceptance thereof and your Notice of Award, shall be binding upon us.

We understand that you are not bound to accept the Lowest Calculated Bid or any Bid you may receive.

We certify/confirm that we comply with the eligibility requirements pursuant to the PBDs.

The undersigned is authorized to submit the bid on behalf of [name of the bidder] as evidenced by the attached [state the written authority].

We acknowledge that failure to sign each and every page of this Bid Form, including the attached Schedule of Prices, shall be a ground for the rejection of our bid.

Name:	
Legal capacity:	
Signature:	
Duly authorized to sign the Bid for and behalf of:	
Date:	

Price Schedule for Goods Offered from Within the Philippines

[Shall be submitted with the Bid if bidder is offering goods from within the Philippines]

For Goods Offered from Within the Philippines

Name of Bidder _____ Project ID No._____ Page ___of___

1	2	3	4	5	6	7	8	9	10
Item	Description	Country of origin	Quantity	Unit price EXW per item	Transportation and all other costs incidental to delivery, per item	Sales and other taxes payable if Contract is awarded, per item	Cost of Incidental Services, if applicable, per item	Total Price, per unit (col 5+6+7+ 8)	Total Price delivered Final Destination (col 9) x (col 4)

Name: _____ Legal Capacity: _____

Signature: _____

Duly authorized to sign the Bid for and behalf of: _____

Statement of Single Largest Completed Contract (SLCC) Similar

Name of Contract/ Project Cost	Date of Contract	Contract Duration	Supplier's Name and Address	Kinds of Goods	Date of Delivery	Contract Amount
			Contract NTD O			

Note: This statement shall be supported with NOA, Contract, NTP O.R or Sales Invoice &. other docs, if necessary

Submitted by: _____

(Printed Name & Signature)

Designation: _____

Company Name: _____

Date: _____

Statement of all Ongoing Government & Private Contracts Including Contracts Awarded But Not Yet Started,

						Am	ount
NameofContract/Project Cost	Date of Contract	Contract Duration	Owner's Name and Address	Kinds of Goods	Date of Delivery	Contract Amount	Value of Outstanding Contract
Government							
Delete							
Private							
						TOTAL	

Note: This statement shall be supported with NOA, Contract, NTP and other docs, if necessary

Submitted by: _____

(Printed Name & Signature)

Designation:

Company Name: _____

Date: _____